

Laboratory Chemical Hygiene Plan

A Policy & Procedures Manual



Northeastern University
Office of Environmental Health & Safety

Revision: Eighth – March 2009

Emergency Phone Numbers

AMUBLANCE / FIRE / POLICE	373-3333
LANE HEALTH CENTER	373-2772
OFFICE OF ENVIRONMENTAL HEALTH AND SAFETY	373-2769
CHEMICAL /INFECTIOUS /RADIOLOGICAL EMERGENCIES	373-3333
POISON INFORMATION CENTER	800-222-1222

RECORD OF AMENDMENTS

DATE	SECTION	AMENDMENT	INITIAL
11/18/94	Cover	Revision date added	SRB
11/18/94	Back Cover	University phone #'s changed	SRB
11/18/94	Table of Contents	Section 1.5 page # / footer added	SRB
11/18/94	1.2	University College added and Respiratory Therapy deleted from plan list	SRB
11/18/94	1.2	Responsibilities changed for Principal Investigator and Dept. Chemical Hygiene Officer / Laboratory Supervisor	SRB
11/18/94	5	New terms added	SRB
9/3/97	1.5.2.3	Information on MSDS link added	SRB
9/3/97	Cover	Acknowledgment section added	SRB
9/3/97	2.3.5.2	Changed check of eyewashes and safety showers from once to twice yearly	SRB
9/3/97	2.5.5	Added availability of mercury vacuum through OEHS	SRB
9/3/97	3.1.2	Added link to OEHS home page	SRB
9/3/97	Appendix A	Mercury and mercury salts added to list	SRB
9/3/97	Appendix F	Last sentence changed to reflect Plan availability on Web	SRB
1/12/99	1.2	Training reference added to PI responsibilities	SRB
1/12/99	1.5.1	Training section revised to address personnel under and over 16 in laboratories	SRB
1/12/99	1.5.2.2	Link to Cornell University label information added	SRB
1/12/99	1.5.2.3	MSDS section updated to reflect OSHA's new policy on Web access to this information	SRB
1/12/99	2.33	Eye Protection Chart reduced in size	SRB
1/12/99	2.5.1	Contingency Plan reference added	SRB
1/12/99	2.8	Hazardous Waste information updated	SRB
2/17/03	Cover	Revision date and Appendices title added	EAG
2/17/03	1.2	Animal Care and Physical Therapy added to NU Departments	SRB
2/17/03	1.2	The PI section revised to address personnel job transfer or termination	EAG
2/17/03	1.2	Added link to EHS home page	SRB
2/17/03	1.5.2	Underage Personnel revised and expanded	JMP
2/17/03	1.5.3.2	Added link to Laboratory Chemical Labeling Requirements sheet	SRB
2/17/03	1.5.3.4	Laboratory Signs section revised	EAG

2/17/03	1.9	Added link to Respiratory Protection Fact Sheet	EAG
2/17/03	1.11	Research Protocol Chemical Safety Review section revised	JMP
2/17/03	2.1.1	Revised and added link to Unattended Experiment Fact Sheet	EAG
2/17/03	2.1.2	Laboratory supervision section added	JMP
2/17/03	2.1.4	Housekeeping revised	EAG
2/17/03	2.4.3	Added link to flammable storage cabinets	EAG
2/17/03	2.4.3.1, 3.2.1	Added link to Peroxidizable Compounds Fact Sheet	EAG
2/17/03	2.6.1	Added link to Cryogenic Liquid Fact Sheet	EAG
2/17/03	2.6.2	Added link to Hydrofluoric Acid Fact Sheet	EAG
2/17/03	2.6.4	Added phone 800 # for Poison Information Center	EAG
2/17/03	2.8	Linked to Hazardous Waste Satellite Accumulation Area Requirements	SRB
2/17/03	3.1.2	Linked to Boston Fire Department Storage Requirements	SRB
2/17/03	3.3.2	Revised and linked to Compressed Gas Management Fact Sheet	EAG
2/17/03	3.3.3	Special Precautions for Cryogenics section added and linked to Cryogenic Liquid Fact Sheet	EAG
2/17/03	3.4.1	Linked to Hydrofluoric Acid Fact Sheet	EAG
2/17/03	5	Glossary Terms Updated	EAG
2/17/03	Appendix b	Revised and updated list of substances known as carcinogens	EAG
2/17/03	Appendix b	Linked to sources of up to date lists of carcinogens at OSHA, IARC & NTP	EAG
2/17/03	Appendix d	Updated laboratory safety references	EAG
9/22/05	1.2	Enhanced and clarified responsibilities for individuals and entities identified in Section 1.2 per Chemical Hygiene Committee	SRB
9/22/05	1.11	This section edited to reflect current requirements and needs	SRB
4/13/06	2.1.3	Updated to reflect to policy approved by the Chemical Hygiene Committee for hygiene in shops.	SRB
4/13/06	3.4.1	Updated to reflect to policy approved by the Chemical Hygiene Committee for use of hydrofluoric acid.	SRB
7/11/06	1.5.2	Updated to reflect to policy approved by the Chemical Hygiene Committee regarding hazardous processes and restriction of key access to underage personnel.	SRB
9/18/07	2.9	Updated to reflect to policy approved by the Chemical Hygiene Committee regarding closing out laboratories.	SRB
11/21/07	1.2	Updated to reflect Department Safety Officer position replacing Department Chemical Hygiene Officer.	SRB
7/28/08	2.1.3	Restriction on use of gloves outside of laboratory further detailed	SRB

7/28/08	2.3.2.1	Reference to employee changed to “lab personnel” and last sentence added.	SRB
3/23/09	2.1.3	Restriction on use of gloves outside of laboratory changed and requirement lab coats must be uncontaminated if worn outside the laboratory added by Chemical Hygiene Committee.	SRB
3/23/09	2.3.2.2	Title of section changed along with the second sentence in the first paragraph and the third sentence in the third paragraph.	SRB
3/23/09	2.6.4	Poison Information Center phone number updated.	SRB

LABORATORY CHEMICAL HYGIENE PLAN

TABLE OF CONTENTS

SECTION	CONTENTS
1	CHEMICAL HYGIENE PLAN: 1.1 Introduction 1.2 Chemical Hygiene Responsibilities 1.3 Definition 1.4 Hazard Identification 1.5 Training and Information 1.6 Chemical Exposure Assessment 1.7 Medical Consultation 1.8 Chemical Fume Hood Evaluation 1.9 Respiratory Protection Program 1.10 Recordkeeping 1.11 Particularly Hazardous Substance Safety Review
2.0	STANDARD OPERATING PROCEDURES FOR WORKING WITH CHEMICALS: 2.1 Good Work Practices for Handling Laboratory Chemicals 2.2 When Not to Proceed Without Safety Procedure Review 2.3 Protective Clothing and Laboratory Safety Equipment 2.4 Chemical Procurement, Distribution, and Storage 2.5 Chemical Spills and Accidents 2.6 Personal Contamination and Injury 2.7 Fire and Related Emergencies 2.8 Chemical Waste Disposal Program
3	HEALTH AND SAFETY INFORMATION FOR WORK WITH CHEMICALS OF SPECIFIC HAZARD CLASS: 3.1 Flammable Liquids 3.2 Highly Reactive Chemicals and High Energy Oxidizers 3.3 Compressed Gases 3.4 Corrosive Chemicals 3.5 Chemicals of High Acute and Chronic Toxicity 3.6 Regulated and Particularly Hazardous Chemicals
4	CHEMICAL TOXICOLOGY 4.1 Chemical Toxicology Overview 4.2 Some Target Organ Effects 4.3 Occupational Health Standards
5	GLOSSARY OF TERMS
APPENDIX A	CHEMICALS REQUIRING PRIOR APPROVAL
APPENDIX B	LIST OF CARCINOGENS

APPENDIX OSHA'S LABORATORY STANDARD
C

APPENDIX LABORATORY SAFETY REFERENCE MATERIAL
D

APPENDIX QUESTIONS AND ANSWERS CONCERNING OSHA'S LABORATORY
E STANDARD

APPENDIX DEPARTMENT STANDARD OPERATING PROCEDURES
F

LABORATORY CHEMICAL HYGIENE PLAN

SECTION 1

CHEMICAL HYGIENE PLAN

1.1 INTRODUCTION

The Occupational Safety and Health Administration's (OSHA) laboratory health standard (Occupational Exposures to Hazardous Chemicals in Laboratories (CFR 1910.1450)) requires employers of laboratory employees to implement exposure control programs and convey chemical health and safety information to laboratory employees working with hazardous materials. Specific provisions of the standard require:

1. laboratory chemical hood evaluations;
2. establishment of standard operating procedures for routine and "high hazard" laboratory operations;
3. research protocol safety reviews;
4. employee exposure assessments;
5. medical consultations/exams;
6. employee training;
7. labeling of chemical containers; and,
8. the management of chemical safety information sheets (Material Safety Data Sheets) and other safety reference materials.

The standard's intent is to ensure that laboratory employees are apprised of the hazards of chemicals in their work area, and that appropriate work practices and procedures are in place to protect laboratory employees from chemical health and safety hazards.

The standard operating procedures (laboratory practices, engineering controls, and use of personal protective equipment) recommended in this manual identify the safeguards that should be taken when working with hazardous materials. These safeguards will protect laboratory workers from unsafe conditions in the vast majority of situations. There are instances, however, when the physical and chemical properties, the proposed use, the quantity used for a particular purpose or the toxicity of a substance will be such that either additional, or fewer, controls might be appropriate to protect the laboratory worker. Professional judgement is essential in the interpretation of these standard operating procedures, and individual laboratories may modify these procedures to meet their specific uses and operational needs.

This document outlines how Northeastern University is complying with each of the elements in OSHA's Laboratory Standard. An official copy of the Chemical Hygiene Plan is located in the Office of Environmental Health and Safety, 229 Forsyth Building.

1.2 CHEMICAL HYGIENE RESPONSIBILITIES

Responsibility for chemical health and safety rests at all levels including the:

President of the University, who has ultimate responsibility for chemical hygiene within the University and must, along with other officials, provide continuing support for chemical safety.

Provost Office: The Provost serves as the chief academic officer of the university, reporting directly to the President as the Senior Vice President for Academic Affairs. He/she is responsible for all academic programs offered by the university and for personnel engaged in carrying out that function. He/she provides leadership in curricular, instructional, and faculty development matters and governs the budgeting, administering, evaluating, and planning of the academic aspects of university life. The Provost also serves as vice chair of the president's cabinet and chair of the Faculty Senate. The Provost designates the Vice Provost for Research to oversee a number of key programs for the development and administration of research and teaching initiatives. The Vice Provost Research appoints an administrative officer to the Chemical Hygiene Committee to represent research administration. Typically this appointment is the Director of Research Integrity.

College Deans report to the Provost. Deans that oversee departments or research centers that operate laboratories shall appoint a representative for the college to the Chemical Hygiene Committee.

Senior Vice President for Administration oversees key administrative operations of the University including Facility Services. The Vice President of Facilities Services oversees key facility maintenance and building service operations that impact laboratory operations. The VP of Facility Services shall appoint a representative to the Chemical Hygiene Committee.

Director of Public Safety oversees campus wide public safety programs including fire safety and emergency response. The Director of Public Safety shall appoint a representative to the Chemical Hygiene Committee.

The Northeastern University Chemical Hygiene Committee reports directly to the President of the University. The Committee is charged with formulating policy and making recommendations related to use of hazardous materials in laboratories.

The Committee shall provide an annual report of activities and recommendations towards the state and improvement of chemical hygiene on the Northeastern University campus.

The chair is selected by the committee on an annual basis. Normally, this is done at the first meeting in September of each year. Normally, a chair's term is for one year. The secretary shall be the NU Chemical Hygiene Officer from the Environmental Health and Safety Office.

Decisions will be made by majority vote.

Office of Environmental Health and Safety (EHS) reports to the President's Office through the General Counsel's Office.

A.) Responsibility:

The Office of Environmental Health and Safety (EHS) is charged with the responsibility for control, review, monitoring and advice with respect to exposure to chemical, radiological, and biological agents used in research and teaching. The office provides oversight and control of physical hazards in the workplace, including general and laboratory safety, and chemical waste disposal.

B.) Authority:

The Office of Environmental Health and Safety has the authority to stop any activity which is immediately hazardous to life or health. Its primary function however, is to act in an advisory capacity to the individual units, and to help them provide a safe and healthy workplace.

C.) Resources:

The Office of Environmental Health and Safety has professional staff who can be called upon for advice and help on occupational safety and environmental health problems. This staff offers the following services relating to chemical hygiene for the University:

- Evaluate and implement safety policies and review new and existing equipment and operating practices to minimize hazards to the University community and visitors from fire, electricity, hazardous materials, explosion, pressure and machinery.
- Conduct accident investigations and suggest remedial measures and procedures.
- Hazardous waste disposal services are provided for chemical, biological and radioactive materials.
- Train and assist in conducting special accident prevention programs are available as required.
- Audit by inspection and visits chemical health and safety in the laboratories.

All members of the University should feel free to consult with the EHS involving potential toxic chemical, microbiological or radiation exposure.

EHS's services are available both in emergency situations and in an advisory capacity to answer questions from anyone at the University. However, procedures for safe use and disposal of chemicals or radioactive substances start in the laboratory; therefore students, post-doctoral fellows and technicians must be informed about their responsibilities and the procedures to be followed by the principal investigator. In the event of an emergency situation, please call Public Safety at x3333.

The N.U. Chemical Hygiene Officer, is a professional staff member of the Office of Environmental Health & Safety and is designated by the Director of the Office of Environmental Health & Safety. The N.U. Chemical Hygiene Officer oversees and manages chemical hygiene for the entire University. These duties are as follows:

- Develop and implement a University wide Chemical Hygiene Plan to ensure consistent and well documented program procedures and policy decisions.
- Work with department chairs and Department Safety Officers to maintain compliance with the Chemical Hygiene Plan. Special attention will be given to the safe procurement, use, and disposal of chemicals.
- Assist principal investigators with arranging training sessions for all laboratory workers including supervisors, faculty, principal investigators, teaching assistants, students, visiting scholars, etc.
- Assist principal investigators with laboratory safety audits. Assistance with documentation (record keeping) of audits and all employee training sessions will also be provided as necessary.

In addition, the N.U. Chemical Hygiene Officer will be responsible for knowing the contents of the relevant regulation (Occupational Exposures to Hazardous Chemicals in Laboratories, 29 CFR 1910.145) and conduct any required updating of the Chemical Hygiene Plan as regulations require.

The N.U. Chemical Hygiene Officer can be reached by calling the Office of Environmental Health and Safety at x2769.

Northeastern University Departments and Research Centers that are required to implement the Chemical Hygiene Plan are as follows:

- Division of Laboratory Animal Medicine
- Barnett Institute
- Biology Department
- Center for Advanced Microgravity Materials Processing CAMMP
- Center for Drug Discovery
- Chemical Engineering
- Chemistry and Chemical Biology
- Civil and Environmental Engineering
- Electrical and Computer Engineering
- CENCIS
- Office of Environmental Health and Safety
- Earth and Environmental Sciences
- Kostas Nanomanufacturing Center
- University Health and Counseling Center
- Nursing
- Marine Science Center (Nahant)
- Mechanical and Industrial Engineering
- Medical Laboratory Science

- New England Center for Tissue Inflammation
- Pharmacy
- Pharmaceutical Sciences
- Physical Therapy
- Physics
- Psychology
- Toxicology (Pharmaceutical Sciences)
- University College Professional and Continuing Studies

Each of these departments conduct laboratory work as defined in the OSHA Laboratory Standard.

Laboratory, means a facility where the laboratory use of hazardous chemicals occurs. It is a workplace where relatively small quantities of hazardous chemicals are used on a non-production basis".

Any department at Northeastern University not listed above will also be required to implement the Chemical Hygiene Plan if laboratory work is conducted.

The Department Safety Committee when it exists reviews and recommends policies that provide for the safe conduct of work involving hazardous chemicals and develops guidelines for reviewing and approving the use of high risk substances in research operations.

The Department Chairperson is responsible for chemical hygiene in the department/unit. Shall maintain and report to EHS at least once per semester or as changes occur, a list of authorized laboratory workers in their unit that are allowed to work in the laboratories. EHS maintains a present list of laboratory workers that will be emailed as reminder at the beginning of each semester to chairs.

The Department Safety Officer has the responsibility of assisting faculty, staff and students serving as a conduit in facilitating, promoting, maintaining a safe work environment and compliance with the regulatory requirements. The DSO works closely with Principal Investigators (PI's) and Laboratory Instructors (LI's) of Record who have the ultimate responsibility for safety in their individual research and teaching laboratories. The Department Safety Officer has the following duties:

- Help to ensure that all work in their department or unit is conducted in accordance with the Chemical Hygiene Plan.
- Assist EHS with disseminating information and raising awareness related to Chemical Hygiene in their department units.
- Assist department or unit faculty with requirements of the Chemical Hygiene Plan as necessary.
- Coordinate with department faculty and staff to ensure all laboratory personnel receive adequate training.
- Follow up with PI's and LI's on violations identified by EHS.

- Conduct periodic self-assessments of teaching laboratories that are under their charge
- Assist PI's and LI's in periodic self-assessments of laboratories.
- Inform students, faculty, and staff of safety and environmental program requirements per EHS and ensure that they are followed.
- Help PI's and LI's develop procedures for responding to emergencies and assessing hazards
- Review procedures with EHS for responding to emergencies and assessing hazards.
- Work with PI's and LI's implement recommendations of EHS.

The Faculty Investigator, or Instructor-in-Charge of teaching laboratories manages chemical hygiene in his or her laboratory and works closely and efficiently with the Departmental Chemical Hygiene Officer (DCHO) and Environmental Health and Safety office to ensure compliance. The Faculty Investigator or Instructor-in-Charge is responsible for:

- Informing employees (laboratory workers) working in their laboratory of the potential hazards associated with the use of chemicals in the laboratory and instructing them in safe laboratory practices, adequate controls, and procedures for dealing with accidents involving hazardous chemicals.
- Selecting and employing laboratory practices and engineering controls that reduce the potential for exposure to hazardous chemicals to the appropriate level.
- Working with EHS and the CHC, to recognize special hazards not covered in the Chemical Hygiene Plan and develop Standard Operating Procedure (SOP) for special hazards or alternative procedures. The SOP shall include a description of the alternative controls that will be used. A 3 ring binder visual in the laboratory book shelves with "Standard Operating Procedures for Special Hazards" on the Spline and Cover is the recommended practice
- Ensuring that all lab personnel have access to protective equipment and clothing necessary for the safe performance of their jobs.
- Working closely and efficiently with the NU Chemical Hygiene Officer to correct work practices and conditions that may result in exposure or release of toxic chemicals.
- Supervising the performance of their staff and authorized personnel to help ensure the required chemical hygiene rules are adhered to in the laboratory.
- Contacting the NU Chemical Hygiene Officer prior to using particularly hazardous substances when special handling conditions are needed if you exceed threshold quantities of a substance that are on the Particularly Hazardous Chemical list.
- Developing an understanding of the current requirements regulating hazardous substances used in his/her laboratory ([see EHS website](#)) and maintaining compliance with these requirements.
- Ensuring that, in case of job transfer or termination, workers shall properly dispose of or transfer all chemicals to another responsible party before leaving.
- When necessary, consulting with EHS to arrange workplace air samples, swipes or other tests to determine the amount and nature of airborne and/or surface

contamination, inform employees of the results, and use data to aid in the evaluation and maintenance of appropriate laboratory conditions.

- Report promptly to the N.U. Chemical Hygiene Officer incidents that cause (1) personnel to be seriously exposed to hazardous chemicals or materials, such as through the inoculation of a chemical through cutaneous penetration, ingestion of a chemical, or probable inhalation of a chemical, or that (2) constitute a danger of environmental contamination.
- Ensuring that co-op students, undergraduate students, high school students, and visitors are directly supervised when present in the laboratory.
- Maintaining a list of authorized personnel who are allowed to work in their laboratories and report this information to their department chair or chemical hygiene officer at least once per semester or as changes occurs.

Laboratory worker, who is responsible for:

- Being aware of the hazards of the materials she/he is around or working with, and handling those chemicals in a safe manner.
- Planning and conducting each operation in accordance with established chemical hygiene procedures.
- Developing good chemical hygiene habits (chemical safety practices and procedures).
- Reporting unsafe conditions to his/her supervisor, the Principal Investigator or the Department Safety Officer.
- In consultation with faculty investigator, properly dispose of or transfer all chemicals to another responsible party before job transfer or termination.

The faculty investigator or instructor-in-charge share responsibility with the laboratory worker for collecting, labeling and storing chemical hazardous waste properly, as well as informing visitors entering their laboratory of the potential hazards and safety rules/precautions.

Student is responsible for:

- Attending required training sessions and following all standard operating procedures of working in a laboratory.
- Wearing personal protective equipment as directed by the principal investigator.
- At a minimum, wearing safety glasses at all times when in the laboratory.
- Reporting to the teaching assistant, faculty member, or Department Safety Officer/laboratory supervisor any accidents that result in the exposure to toxic chemicals, and/or any action or condition that may exist which could result in an accident.

1.3 DEFINITIONS

1.3.1 Laboratory Definition

For the purposes of this OSHA standard a laboratory is defined as a facility in which hazardous chemicals (defined below) are handled or manipulated in reactions, transfers, etc. in small quantities (containers that are easily manipulated by one person) on a non-production basis. Typically, multiple chemical procedures are used.

1.3.2 Hazardous Chemical Definition

The OSHA Laboratory Health Standard defines a hazardous chemical as any element, chemical compound, or mixture of elements and/or compounds which is a physical or a health hazard. The standard applies to all hazardous chemicals regardless of the quantity.

A chemical is a physical hazard if there is scientifically valid evidence that it is a combustible liquid, a compressed gas, an explosive, an organic peroxide, an oxidizer or pyrophoric, flammable, or reactive.

A chemical is a health hazard if there is statistically significant evidence, based on at least one study conducted in accordance with established scientific principles, that acute or chronic health effects may occur in exposed employees. Classes of health hazards include:

- * carcinogens
- * reproductive toxins
- * sensitizers
- * hepatotoxins (liver)
(kidney)
- * agents that act on the hematopoietic system (blood)
- * agents that damage the lungs, skin, eyes, or mucus membranes
- * irritants
- * corrosives
- * neurotoxins (nerve)
- * nephrotoxins

A chemical is considered a carcinogen or potential carcinogen. if it is listed in any of the following publications (OSHA uses the term "select" carcinogen):

- National Toxicology Program, Annual Report on Carcinogens (latest edition)
- International Agency for Research on Cancer, Monographs (latest edition)
- OSHA, 29 CFR 1910.1001 to 1910.1101, Toxic and Hazardous Substances

A chemical is considered hazardous, according to the OSHA standard, if it is listed in any of the following:

- OSHA, 29 CFR 1910.1000 Table Z-1 through Z-3
- Threshold Limit Values for Chemical Substances and Physical Agents in the Work Environment, ACGIH (latest edition)
- The Registry of Toxic Effects of Chemical Substances, NIOSH (latest edition)
- Over 600,000 chemicals are considered hazardous by the OSHA definition.
- In most cases, the chemical container's original label will indicate if the chemical is hazardous. Look for key words like caution, hazardous, toxic, dangerous, corrosive, irritant, carcinogen, etc. Containers of hazardous chemicals acquired or manufactured before 1985 may not contain appropriate hazard warnings.

- If you are not sure a chemical you are using is hazardous, review the Material Safety Data Sheet for the substance or contact your supervisor.

1.4 HAZARD IDENTIFICATION

Some laboratories may synthesize or develop new chemical substances on occasion. If the composition of the substance is known and will be used exclusively in the laboratory, the laboratory worker must label the substance and determine, to the best of his/her abilities, the hazardous properties (e.g., corrosive, flammable, reactive, toxic, etc.) of the substance. This can often be done by comparing the structure of the new substance with the structure of similar materials with known hazardous properties. If the chemical produced is of unknown composition, it must be assumed to be hazardous, and appropriate precautions taken.

If a chemical substance is produced for another user outside this facility, the laboratory producing the substance is required to provide as much information as possible regarding the identity and known hazardous properties of the substance to the receiver of the material.

1.5 TRAINING & INFORMATION

1.5.1 Chemical Safety Training

All faculty, staff, and graduate students who work in any laboratory where hazardous chemicals are stored or used must complete the required safety awareness programs appropriate for the operations conducted in that laboratory. As a minimum, all personnel must complete the Chemical Hygiene training program offered through EHS. Other safety awareness training may include Hazardous Waste, Radiation Safety, and Biological Safety. The principal investigator of the laboratory is responsible to ensure that all laboratory personnel complete the required training. In addition, principal investigators must ensure that co-op students, undergraduate students, high school students, and visitors are sufficiently informed and aware of potential hazards in the lab and receive appropriate safety awareness training.

Our training program for laboratory workers consists of two parts: 1) introduction to the standard and to information not specific to the individual worksite to be conducted by the Office of Environmental Health and Safety, and 2) site specific elements of training to be conducted by the Principal Investigator. The training and information will be provided when an employee is initially assigned to a laboratory where hazardous chemicals are present, and also prior to assignments involving new hazardous chemicals and/or new laboratory work procedures (Note training schedule and on-line options).

The training and information program will describe the:

1. physical and health hazards of various classes of laboratory chemicals handled;

2. methods/procedures for safely handling and detecting the presence or release of hazardous chemicals present in the laboratory;
3. appropriate response in the event of a chemical emergency (spill, overexposure, etc.);
4. chemical safety policies; and
5. applicable details of the Chemical Hygiene Plan (such as the standard operating procedures for using chemicals).

When an employee is to perform a non-routine task presenting hazards for which he or she has not already been trained, the employee's supervisor will be responsible for discussing with the employee the hazards of the task and any special measures (e.g., personal protective equipment or engineering controls) that should be used to protect the employee.

Every laboratory worker should know the location and proper use of needed or necessary protective clothing and equipment, and emergency equipment/procedures. Information on protective clothing and equipment is contained in Section 2.3 of this manual.

1.5.2 Underage Personnel

Any person under the age of 16 will generally not be allowed to work in a laboratory where hazardous processes take place, or hazardous chemicals are stored or used. The NU Chemical Hygiene Officer must approve any exceptions to this requirement. For laboratories that utilize radioactive materials, no one under the age of 18 is allowed to work in the laboratory. Underage personnel, including high school students or visitors, must be directly supervised by faculty, staff or graduate students at all times. No key or key access should be granted to underage personnel

1.5.3 Chemical Safety Information Sources

There are numerous sources of chemical safety information. These sources include:

1. special health and safety reference literature available in the Snell Library and the Office of Environmental Health and Safety;
2. the labels found on containers of hazardous chemicals;
3. the substance's Material Safety Data Sheet; and
4. laboratory signs.

In addition, your supervisor is available to provide safety information. Each of these sources is now discussed in greater detail.

1.5.3.1 Safety Reference Literature

The Office of Environmental Health and Safety maintains a library of reference materials addressing chemical health and safety issues. One of the references contains all applicable chemical workplace exposure standards and recommended exposure levels. Another reference contains a copy of OSHA's laboratory safety standard and its appendices.

Material Safety Data Sheets received from suppliers are available in your laboratory or a central area designated by your department. MSDS's can also be accessed from the following URL: http://www.ehs.neu.edu/laboratory_safety/material_safety/.

1.5.3.2 Container Labeling

All containers of hazardous chemicals that could pose a physical or health hazard to an exposed employee must have a label attached. Labels on purchased hazardous chemicals must include:

1. the common name of the chemical;
2. the name, address and emergency phone number of the company responsible for the product; and
3. an appropriate hazard warning.

The warning may be a single word - "danger", "warning" and "caution" - or may identify the primary hazard, both physical (i.e., water reactive, flammable or explosive) and health (i.e., carcinogen, corrosive, or irritant).

Most labels will provide you with additional safety information to help you protect yourself while working with this substance. This includes protective measures to be used when handling the material, clothing that should be worn, first aid instructions, storage information and procedures to follow in the event of a fire, leak or spill.

If you find a container with no label, report it to your supervisor. You should also report labels that are torn or illegible so that the label can be replaced immediately. Existing labels on new containers of hazardous chemicals should never be removed or defaced, except when empty! If you use secondary working containers that will take more than one work shift to empty, or if there is a chance that someone else will handle the container before you finish it, you must label it. This is part of your responsibility to help protect co-workers. If you need labels for these types of containers, [Cornell University](#) has an excellent site for printing up your own chemical labels.

Read the label each time you use a newly purchased chemical. It is possible the manufacturer may have added new hazard information or reformulated the product since your last purchase, and thus altered the potential hazards you face while working with the product.

All employees involved in unpacking chemicals are responsible for inspecting each incoming container to insure that it is labeled with the information outlined above. The principal investigators or Department Safety Officer/laboratory supervisors should be notified if containers do not have proper labels ([see laboratory chemical labeling requirements](#)).

1.5.3.3 Material Safety Data Sheets

A Material Safety Data Sheet, often referred to by its acronym MSDS, is a detailed informational document prepared by the manufacturer or importer of a hazardous chemical that describes the physical and chemical properties of the product. Information included in a Material Safety Data Sheet aids in the selection of safe products, helps employers and employees understand the potential health and physical hazards of a chemical and describes how to respond effectively to exposure situations. [Material Safety Data Sheets](#) can be accessed through the Office of Environmental Health and Safety Web Site. All laboratory personnel within a research group must be able to access this site 24/7 or they will be required to keep hard copies of MSDS's for each chemical they use or store in the laboratory. As a back-up to this site, the Office of Environmental Health and Safety maintains hard copies of MSDS's in its office located in 229 Forsyth Building.

The format of a Material Safety Data Sheet may vary but there is specific information that must be included in each sheet. It is useful to review this information to increase your ability to use a Material Safety Data Sheet.

All Material Safety Data Sheets should include the following information:

Section I of the MSDS lists information identifying the manufacturer and the product.

- Manufacturer's name, address and telephone number
- Number to call in case of emergency involving product
- Chemical name and synonyms
- Trade name and synonyms
- Chemical family and formula
- CAS number (Chemical Abstract Service) for pure materials

Section II describes the various hazardous ingredients contained in the product, the percentages, and exposure limits when appropriate. All hazardous chemicals that comprise 1% or greater of the mixture will be identified. Carcinogens will be listed if their concentrations are 0.1% or greater. If a component is not listed, it has been judged to be non-hazardous or is considered proprietary information by the manufacturer. The types of components that might be listed include:

- o Pigments, catalysts, vehicles, solvents, additives, others
- o Base metals, alloys, metallic coatings, fillers, hazardous mixtures of other liquids, solids or gases

Section III describes the physical properties of the material.

- Boiling point
- Vapor pressure
- Vapor density
- Solubility in water
- Specific gravity
- Percent volatile
- Evaporation rate
- Appearance and odor

Section IV describes the fire and explosion hazard data for the material. Based on the flash point and other fire and explosion data, the appropriate extinguishing agent for fires involving the material will be listed. Special procedures may also be listed.

- Flash point
- Lower and upper explosive limits (LEL/UEL)
- Extinguishing agent - water, dry chemical, foam, halon, etc.
- Unusual fire and explosion hazards, toxic fumes

Section V describes the known health hazards associated with the material, applicable exposure limits and symptoms/health effects associated with overexposure. This information will help the user and medical personnel recognize if an overexposure has occurred.

Threshold Limit Value

- Effects of overexposure: headache, nausea, narcosis, irritation, weakness, etc.
- Primary routes of exposure: inhalation, skin, ingestion
- Cancer or other special health hazards
- Emergency and first aid procedures for ingestion, inhalation and skin or eye contact

Section VI describes reactivity data; that is, the material's ability to react and release energy or heat under certain conditions or when it comes in contact with certain substances.

- Stability: stable, unstable, conditions to avoid
- Incompatibility: materials to avoid
- Hazardous decomposition products
- Hazardous polymerizations: conditions to avoid

Section VII gives instructions for the steps to be taken in case of an accidental release or spill. The steps normally include information on containment, evacuation procedures and waste disposal as appropriate. The statements on the Material Safety Data Sheet are very general; more specific information is available from your supervisor or the Department Safety Officer/Laboratory Supervisor.

- Steps to be taken in case material is released or spilled
- Waste disposal methods

Section VIII describes the protective equipment for the individual who might have to work with the substance. This section normally describes worst case conditions; therefore, the extent to which personal protective equipment is required is task dependent. Contact your supervisor or Department Safety Officer/Laboratory Supervisor for specific instructions if you are unsure.

- Respiratory equipment: dust mask, chemical cartridge respirator, self-contained breathing apparatus
- Ventilation: local, general, special
- Protective gloves: type, fabrication material
- Eye protection: goggles, face shield
- Other protective equipment

Section IX describes handling and storage procedures to be taken with the material. Information may include statements, such as: keep container closed; store in a cool, dry, well ventilated area, keep refrigerated (caution: flammable solvents require a "flammable storage refrigerator"), avoid exposure to sunlight, etc.

Section X describes any special precautions or miscellaneous information regarding the material.

Manufacturers may withhold certain information as proprietary (such as hazardous ingredients) on a Material Safety Data Sheet if the information is considered a trade secret. The Chemical Hygiene Officer has a legal right to obtain this information from the manufacturer to evaluate the potential health risk if potential overexposure or adverse health effects are suspected.

1.5.3.4 Laboratory Signs

Prominent signs of the following types should be posted in each laboratory:

- NFPA hazardous warning information and telephone numbers of emergency personnel/facilities, supervisors, and laboratory workers;
- Signs identifying locations of safety showers, eyewash stations, other safety and first aid equipment, and exits;
- Warnings at areas or equipment where special or unusual hazards exist; and
- Laboratory posting for [Prohibited Wastewater Discharges](#).
- Laboratory posting for [Hazardous Waste Satellite Accumulation Area](#).

1.6 CHEMICAL EXPOSURE ASSESSMENT

Regular environmental or employee exposure monitoring of airborne concentrations is not usually warranted or practical in laboratories because chemicals are typically used for relatively short time periods and in small quantities. However, sampling may be appropriate when a highly toxic substance is either used regularly (3 or more separate handling sessions per week), used for an extended period of time (greater than 3 to 4 hours at a time), or used in especially large quantities. Notify the N.U. Chemical Hygiene Officer if you are using a highly toxic substance in this manner.

The exposures to laboratory employees who suspect and report that they have been overexposed to a toxic chemical in the laboratory, or are displaying symptoms of overexposure to toxic chemicals, will also be assessed. The assessment will initially be

qualitative and, based upon the professional judgment of the N.U. Chemical Hygiene Officer, may be followed up by specific quantitative monitoring. A memo, or report, documenting the assessment will be sent to the employees involved and their supervisors within fifteen days of receipt of the results. A copy will be stored in a central exposure records file maintained by the Office of Environmental Health and Safety.

Individual concerns about excessive exposures occurring in the laboratory should be brought to the attention of your supervisor or the N.U. Chemical Hygiene Officer immediately.

1.7 MEDICAL CONSULTATION & EXAMINATION

Northeastern University will provide employees who work with hazardous chemicals an opportunity to receive medical attention, including any follow-up examinations, which the examining physician determines to be necessary, whenever an employee:

- develops signs or symptoms associated with excessive exposure to a hazardous chemical used in their laboratory;
- is exposed routinely above the action level (or in the absence of an action level, the applicable OSHA work place exposure limit) of an OSHA regulated substance;
- may have been exposed to a hazardous chemical during a chemical incident such as a spill, leak, explosion or fire; and
- is referred for medical follow up by the N.U. Chemical Hygiene Officer.

Individuals with life threatening emergencies should dial Public Safety at x3333 for emergency transport to the hospital. All accidents resulting in injuries, which require medical treatment (including first aid) should be reported immediately to your supervisor and the N.U. Chemical Hygiene Officer. Medical examination/consultation visits (non-life threatening) will be handled by the Lane Health Center (LHC). Appointments can be arranged by contacting the LHC staff at x2772. Medical exams and consultations shall be done by or under direct supervision of a licensed physician at no cost to the employee.

Where medical consultations or examinations are provided, the examining physician shall be provided with the following information:

1. the identity of the hazardous chemical(s) to which the employee may have been exposed;
2. the exposure conditions; and
3. the signs and symptoms of exposure the laboratory employee is experiencing, if any.

1.8 CHEMICAL (FUME) HOOD EVALUATION

Every laboratory ventilation hood used for the control of air contaminants shall be tested once per year to assure that adequate airflow is being maintained to provide continued protection against employee over-exposure to hazardous materials. The Office of

Environmental Health and Safety is responsible for performing this testing. Laboratory hood airflow shall be considered adequate when the average face velocity equals a minimum of a 100 feet/minute and a maximum of 125 feet/minute with the hood sash at a working height (14 to 20 inches). Other local exhaust ventilation, such as instrument vents, will also be tested. The criteria for minimal acceptable flow shall be determined by the Office of Environmental Health and Safety. Results of laboratory ventilation tests shall be recorded and maintained by the Office of Environmental Health and Safety.

1.9 RESPIRATORY PROTECTION PROGRAM

Northeastern University attempts to minimize employee respiratory exposure to potentially hazardous chemical substances through engineering methods (such as local exhaust ventilation) or administrative control. It is recognized, however, that for certain situations or operations, the use of these controls may not be feasible or practical. Under these circumstances, or while such controls are being instituted, or in emergency situations, the use of personal respiratory protective equipment may be necessary. A sound and effective program is essential to assure that the personnel using such equipment are adequately protected ([See Respiratory Protection fact sheet](#)).

Northeastern University has adopted a written plan for using respirators. This plan outlines organizational responsibilities for the following respirator program components: exposure assessment; respirator selection; medical approval and surveillance; fit testing; user training; inspection/repair; cleaning/disinfection; and storage. Each of these program components is required by OSHA's respiratory protection standard (29 CFR 1910.134) in all situations where respirators are used. If you are using a respirator and are not included in the respirator protection program, or have questions concerning the use of respirators or any of the program components, contact your supervisor or the N.U. Chemical Hygiene Officer.

1.10 RECORDKEEPING

All exposure assessments and occupational medical consultation/examination reports will be maintained in a secure area in accordance with OSHA's medical records rule (29 CFR 1910.20). Individuals may obtain copies or read their reports by making a request in writing to the Office of Environmental Health and Safety (exposure assessment records) or the Lane Health Center (occupational medical records).

1.11 RESEARCH PROTOCOL CHEMICAL SAFETY REVIEW

Under some circumstances a particular chemical substance and associated laboratory operation, procedure or activity may be considered sufficiently hazardous to require prior approval from the Office of Environmental Health and Safety before research begins. This approval process will ensure that safeguards are properly set up and that personnel are adequately trained in the procedure. A list of chemicals and threshold quantities requiring review and approval is located in Appendix A. Laboratory employees anticipating use of

these materials in a manner requiring review must notify the Office of Environmental Health and Safety.

The Northeastern University Chemical Hygiene Officer will visit the laboratory, conduct a survey of facility controls and review the research protocol. The Northeastern University Chemical Hygiene Officer will consult with safety experts as needed to conduct a risk assessment and will submit a report identifying required work practices/controls for conducting the procedure in a safe manner. However, in the event that a recommendation to prohibit the research procedure is made, work will not be allowed to start. Any additional review of the protocol will need to be made to the Chemical Hygiene Committee.

SECTION 2

STANDARD OPERATING PROCEDURES FOR WORKING WITH CHEMICALS

2.1 GOOD WORK PRACTICES/PROCEDURES FOR HANDLING LABORATORY CHEMICALS

2.1.1 General Guidelines

Carefully read the label before using a chemical. The manufacturer's or supplier's Material Safety Data Sheet (MSDS) will provide special handling information. Be aware of the potential hazards existing in the laboratory and the appropriate safety precautions. Know the location and proper use of emergency equipment, the appropriate procedures for responding to emergencies, and the proper methods for storage, transport and disposal of chemicals within the facility.

Do not work alone in the laboratory. If you must work alone or in the evening, let someone else know and have them periodically check on you.

Anyone considering running an experiment unattended should consider the possible hazards that could occur as a result of failures, malfunctions, operational methods, environments encountered, maintenance error and operator error (see [Unattended Equipment Fact Sheet](#)).

Label all secondary chemical containers with appropriate identification and hazard information (see Section I, Container Labeling).

Use only those chemicals for which you have the appropriate exposure controls (such as a chemical fume hood) and administrative programs/procedures (training, restricted access, etc.). Always use adequate ventilation with chemicals. Operations using large quantities (500 milliliters) of volatile substances with workplace standards at or below 50 ppm should be performed in a chemical fume hood.

Use hazardous chemicals and all laboratory equipment only as directed or for their intended purpose.

Inspect equipment or apparatus for damage before adding a hazardous chemical. Do not use damaged equipment.

Inspect personal protective apparel and equipment for integrity or proper functioning before use.

Malfunctioning laboratory equipment (hood) should be labeled or tagged "out of service" so that others will not inadvertently use it before repairs are made.

Handle and store laboratory glassware with care. Do not use damaged glassware. Use extra care with Dewar flasks and other evacuated glass apparatus; shield or wrap them to contain chemicals or fragments should implosion occur.

Do not purchase or dispense more of a hazardous chemical than is needed for immediate use.

2.1.2 Supervision

1. Departments that utilize and maintain teaching/research laboratories and workshops on campus; or conduct related activities at off campus sites; are responsible for implementing applicable safety programs to ensure that these work areas in full compliance with regulatory requirements.
2. To ensure that liability risk is properly managed, qualified supervisors must fulfill their inherent responsibilities to ensure that all activities with hazardous materials and/or in potentially hazardous work environments are done in compliance with environmental/occupational health regulations.
3. Qualified supervisors need to be Northeastern University employees who actively participate in the applicable safety programs by attending safety training/awareness sessions. They are assigned responsibility and authority from their department to conduct routine safety audits of work areas, provide oversight of all activities in assigned work areas, and take necessary action to abate unsafe activities or conditions. Qualified supervisors can include faculty, staff, and graduate students.
4. Visitors, high school and undergraduate students, and any other 'non-employee' must be properly supervised at all times when working in laboratories and workshops.
5. Everyone who is allowed access to a laboratory or workshop must be provided with the applicable safety awareness information by the area/project supervisor or must attend a scheduled training session provided by the department or the office of Environmental Health & Safety.
6. Departments must ensure that proper supervision is provided during Northeastern University affiliated activities conducted off campus. Do not work alone in the laboratory. If you must work alone or in the evening let someone else know and have them periodically check on you.

2.1.3 Personal Hygiene

After working with potentially hazardous materials, remove contaminated personal protective equipment, such as lab coats and disposable gloves. Then, wash your hands. If a sink is not readily available, a waterless hand cleaner may be suitable until a hand washing sink can be used. **Please note:** wearing potentially contaminated gloves or other personal protective equipment outside the designated laboratory space can result in exposures to items and surfaces in public and common areas. Lab coats worn outside of the laboratory

must be uncontaminated, and use is restricted within the building where your laboratory is located. Even if your gloves are not contaminated, recognize that other people do not know this. They will assume that your gloves are contaminated.

If you need to transport research samples, stock chemicals, or other hazardous materials between laboratories, utilize some type of secondary containment or laboratory cart so you won't need to wear gloves or other personal protective equipment. If a protocol requires wearing of gloves outside of the laboratory, it must receive approval of the relative safety committee.

Always avoid direct contact with any chemical. Keep chemicals off your hands, face and clothing, including shoes. Never smell, inhale or taste a hazardous chemical. Wash hands thoroughly with soap and water after handling any chemical. To minimize the risk of exposure, smoking, drinking, eating, and/or the application of cosmetics is forbidden in laboratories or shops where hazardous chemicals are used. A designated area for eating may be set aside in areas that are physically separated from the laboratory or shop. **Never pipette by mouth.** Use a pipette bulb or other mechanical pipette filling device.

2.1.4 Housekeeping

Keep floors clean and dry.

Keep all aisles, hallways, and stairs clear of all chemicals. Stairways and hallways should not be used as storage areas.

Keep all work areas, and especially work benches, clear of clutter and obstructions.

All working surfaces should be cleaned regularly.

Access to emergency equipment, utility controls, showers, eyewashes and exits should never be blocked.

Wastes and broken glassware should be kept in the appropriate containers and labeled properly.

Any unlabeled containers must be labeled if it is not under your supervision or at the end of each working day.

2.2 WHEN NOT TO PROCEED WITHOUT REVIEWING SAFETY PROCEDURES

Sometimes laboratory workers should not proceed with what seems to be a familiar task. Hazards may exist that are not fully recognized. Certain indicators (procedural changes) should cause the employee to stop and review the safety aspects of their procedure. These indicators include:

- A new procedure, process or test, even if it is very similar to older practices.
- A change or substitution of any of the ingredient chemicals in a procedure.
- A substantial change in the amount of chemicals used (scale up of experimental procedures); usually, one should review safety practices if the volume of chemicals used increases by 200%.
- A failure of any of the equipment used in the process, especially safeguards such as chemical hoods.
- Unexpected experimental results (such as a pressure increase, increased reaction rates, unanticipated byproducts). When an experimental result is different from the predicted, a review of how the new result impacts safety practices should be made.
- Chemical odors, illness in the laboratory staff that may be related to chemical exposure or other indicators of a failure in engineered safeguards.

The occurrence of any of these conditions should cause the laboratory employee to pause, evaluate the safety implications of these changes or results, make changes as necessary and proceed cautiously.

2.3 PROTECTIVE CLOTHING AND LABORATORY SAFETY EQUIPMENT

2.3.1 General Consideration - Personal Protective Clothing/Equipment

Personal protective clothing and equipment should be selected carefully and used in situations where engineering and administrative controls cannot be used or while such controls are being established. These devices are viewed as less protective than other controls because they rely heavily on each employee's work practices and training to be effective. The engineering and administrative controls which should always be considered first when reducing or eliminating exposures to hazardous chemicals include:

- **Substitution** of a less hazardous substance
- **Scaling down size of experiment**
- **Substitution** of less hazardous equipment or process (e.g., safety cans for glass bottles)
- **Isolation** of the operator or the process
- **Local and general ventilation** (e.g., use of fume hoods)

The Material Safety Data Sheet (MSDS) will list the personal protective equipment (PPE) recommended for use with the chemical. The MSDS addresses worst case conditions. Therefore, all the equipment shown may not be necessary for a specific laboratory scale task.

Your supervisor, other sections of this manual or the N.U. Chemical Hygiene Officer can assist you in determining which personal protective devices are required for each task. Remember, there is no harm in being overprotected. Appropriate personal protective equipment will be provided to employees.

2.3.2 Protection of Skin and Body

Skin and body protection involves wearing protective clothing over all parts of the body, which could become contaminated with hazardous chemicals. Personal protective equipment (PPE) should be selected on a task basis, and checked to ensure it is in good condition prior to use (e.g., no pinholes in gloves).

2.3.2.1 Normal clothing worn in the laboratory

Where there is no immediate danger to the skin from contact with a hazardous chemical it is still prudent to select clothing to minimize exposed skin surfaces. Laboratory personnel should wear long sleeved/long legged clothing and avoid short sleeved shirts, short trousers or skirts. A laboratory coat should be worn over street clothes and be laundered regularly. A laboratory coat is intended to prevent contact with dirt, chemical dusts and minor chemical splashes or spills. If it becomes contaminated, it should be removed immediately and the affected skin surface washed thoroughly. Shoes should be worn in the laboratory at all times. Sandals and perforated shoes are not appropriate. In addition, long hair and loose clothing should be confined. When personnel are in laboratories that are actively handling hazardous chemicals, use of appropriate clothing and personal protective equipment will be strictly enforced.

2.3.2.2 Protective clothing and equipment

Additional protective clothing may be required for some types of procedures or with specific substances (such as when carcinogens, cryogenics or large quantities of corrosives, oxidizing agents or organic solvents are handled). Personal protective clothing and equipment, sometimes just called personal protective equipment (PPE), may include impermeable aprons, face shield and gloves as well as plastic coated coveralls, shoe covers, and arm sleeves. Protective sleeves should always be considered when wearing an apron. These garments can either be washable or disposable in nature. They should never be worn outside the laboratory. The choice of garment depends on the degree of protection required and the areas of the body, which may become contaminated. Rubberized aprons, plastic coated coveralls, shoe covers, and arm sleeves offer much greater resistance to permeation by chemicals than laboratory coats and, therefore, provide additional time to react (remove the garment and wash affected area) if contaminated.

For work where contamination is possible, special attention must be given to sealing all openings in the clothing. Tape can be utilized for this purpose. In these instances caps should be worn to protect hair and scalp from contamination.

Chemical resistant and special gloves should be worn whenever the potential for contact with corrosive, cryogen or toxic substances and substances of unknown toxicity exists. Gloves should be selected on the basis of the materials being handled, the particular hazard involved, and their suitability for the operation being conducted. Before each use, gloves should be checked for integrity. Gloves should be washed prior to removal whenever possible to prevent skin contamination upon removal. Non-disposable gloves should be replaced periodically, depending on frequency of use and their resistance to the substances handled.

Protective garments are not equally effective for every hazardous chemical. Some chemicals will "break through" the garment in a very short time. Therefore, garment and glove selection is based on the specific chemical utilized. General selection criteria is as follows:

GLOVE TYPE SELECTION GUIDE					
CHEMICAL FAMILY	BUTYL RUBBER	NEOPRENE	PVC (VINYL)	NITRILE	NATURAL LATEX
Acetates	G	NR	NR	NR	NR
Acids, inorganic	G	E	E	E	E
Acids, organic	E	E	E	E	E
Acetonitrile, Acrylonitrile	G	E	G	S	E
Alcohols	E	E	NR	E	E
Aldehydes	E	G	NR	S*	NR
Amines	S	NR	NR	F	NR
Bases, inorganic	E	E	E	E	E
Ethers	G	F	NR	E	NR
Halogens (liquids)	G	NR	F	E	NR
Inks	G	E	E	S	F
Ketones	E	G	NR	NR	G
Nitro compounds (Nitrobenzene, Nitromethane)	G	NR	NR	NR	NR
Oleic Acid	E	E	F	E	NR
Phenols	E	E	NR	NR	G
Quinones	NR	E	G	E	E
Solvents, Aliphatic	NR	NR	F	G	NR

Solvents, Aromatic	NR	NR	F	F	NR
--------------------	----	----	---	---	----

**Not recommended for Acetaldehyde, use Butyl Rubber*

S - Superior E - Excellent G - Good F - Fair NR - Not Recommended

Contact the NU Chemical Hygiene Officer for personal protection equipment selection assistance or information.

2.3.3 Protection of the Eyes

Eye protection is required for all personnel and any visitors present in locations where chemicals are handled and a chemical splash hazard exists. Safety glasses, goggles and goggles with face shield should be worn in the laboratory based upon the physical state, the operation or the level of toxicity of the chemical used. Safety glasses effectively protect the eye from solid materials (dusts and flying objects) but are less effective at protecting the eyes from chemical splash to the face. Goggles should be worn in situations where bulk quantities of chemicals are handled and chemical splashes to the face are possible. Goggles form a liquid-proof seal around the eyes, protecting them from a splash. When handling highly reactive substances or large quantities of hazardous chemicals, corrosives, poisons and hot chemicals, goggles with face shield should be worn.

Contact lenses can increase the risk of eye injury if worn in the laboratory - particularly if they are of the gas permeable variety. Gases and vapors can be concentrated under such lenses and cause permanent eye damage. Chemical splashes to the eye can get behind all types of lenses. Once behind a lens the chemical is difficult to remove with a typical eye wash. For these reasons it is recommended that contact lenses not be worn in laboratories.

Eye and face injuries are prevented by the use of the following:

COMPARISON CHART -- EYE PROTECTION DEVICES									
TYPE	FRONT SPLASH Protection	SIDE SPLASH Protection	FRONT FLYING OBJECT IMPACT Protection	SIDE IMPACT Protection	NECK, FACE Protection	COMFORT TO WEARER	USER ACCEPTANCE	USE LIFETIME	COST
Goggles	Excellent	Excellent	Excellent	Excellent	Poor	Fair	Poor	Fair	Moderate
Glasses (no shields)	Good	Poor	Excellent	Poor	Poor	Good to very good	Very good	Very good	Moderate
Glasses (shields)	Good	Good	Good	Fair	Poor	Good	Good	Very good	Moderate
Face shield (various sizes)	Excellent	Good to excellent	Excellent (if adequate thickness)	Good to excellent	Depends on type and length	Fair	Good for short periods	Fair	Moderate (depending on type)

SOURCE: ANSI Z87.1(1989) Occupational and Educational Eye and Face Protection, available from American National Standards Institute, Inc., 1430 Broadway, New York, N.Y. 10018

2.3.4 Protection of the Respiratory System

Inhalation hazards can be controlled using ventilation or respiratory protection. Check the label and MSDS for information on a substance's inhalation hazard and special ventilation requirements. When a potential inhalation hazard exists, a substance's label or MSDS contains warnings such as:

- Use with adequate ventilation
- Avoid inhalation of vapors
- Use in a fume hood
- Provide local ventilation

Take appropriate precautions before using these substances. Controlling inhalation exposures via engineering controls (ventilation) is always the preferred method (See Section 2.3.5.1). As with other personal protective equipment, respiratory protection relies heavily on employee work practices and training to be effective.

Use of Respirators

Respirators are designed to protect against specific types of substances in limited concentration ranges. Respirators must be selected based on the specific type of hazard (toxic chemical, oxygen deficiency, etc.), the contaminant's anticipated airborne concentration, and required protection factors.

Types of respiratory protective equipment include:

- Particle-removing air purifying respirators
- Gas and vapor-removing air purifying respirators
- Atmosphere supplying respirators

Respirators are not to be used except in conjunction with a complete respiratory protection program as required by OSHA. If your work requires the use of a respirator, contact your supervisor or the N.U. Chemical Hygiene Officer. See Section 1.9 for additional information.

2.3.5 Laboratory Safety Equipment

2.3.5.1 Chemical (Fume) Hoods

In the laboratory, the chemical hood is the primary means of controlling inhalation exposures. Hoods are designed to retain vapors and gases released within them, protecting the laboratory employee's breathing zone from the contaminant. This protection is accomplished by having a curtain of air (approximately 100 linear feet per minute) move constantly through the face (open sash) of the hood. Chemical hoods can also be used to isolate apparatus or chemicals that may present physical hazards to employees. The closed sash on a hood serves as an effective barrier to fires, flying objects, chemical splashes or spattering and small implosions and explosions. Hoods can also effectively contain spills which might occur during dispensing procedures particularly if trays are placed in the bottom of the hoods.

When using a chemical fume hood keep the following principles of safe operation in mind:

- Keep all chemicals and apparatus at least six inches inside the hood (behind sash).
- Hoods are not intended for storage of chemicals. Materials stored in them should be kept to a minimum. Stored chemicals should not block vents or alter air flow patterns.
- Keep the hood sash at a minimum height (4 to 6 inches) when not manipulating chemicals or adjusting apparatus within the hood.
- When working in front of a fume hood, make sure the sash opening is appropriate. This can be achieved by lining up to arrows placed on the sash door and hood frame. This sash opening will ensure an adequate air velocity through the face of the hood.
- Do not allow objects such as paper to enter the exhaust ducts. This can clog ducts and adversely affect their operation.

Follow the chemical manufacturer's or supplier's specific instructions for controlling inhalation exposures with ventilation (chemical fume hood) when using their products. These instructions are located on the products MSDS and/or label. However, it should be noted that these ventilation recommendations are often intended for non-laboratory work environments and must be adapted to suit the laboratory environment as well as the specific procedure or process.

If specific guidance is not available from the chemical manufacturer or supplier, or if the guidance is inappropriate for the laboratory environment, contact the N.U. Chemical Hygiene Officer and/or review the hood use guidelines in the table below. These guidelines are based on information readily available on a chemical's MSDS:

1. applicable workplace exposure standards [Threshold Limit Values (TLV) or Permissible Exposure Limits (PEL)];
2. acute and chronic toxicity data (LD₅₀ and specific organ toxicity); and
3. potential for generating airborne concentrations (vapor pressure).

These terms are defined in the glossary at the back of this manual. The guidelines outlined in the table below should not be considered as necessary or appropriate in every case, but as reasonable "rules of thumb".

Guidelines For Chemical (Fume) Hood Use

It may be appropriate to use a hood when handling the type of substance listed in column 1 if the exposure standard or toxicological criteria in column 2 applies.

Column 1 Type Substance & Handling Procedure	Column 2 Exposure Standard or Toxicity of Substance
Substance handled is solid, liquid or gaseous and when other effective controls are not being used.	TLV or PEL < 5 ppm (vapor) or < 0.2 mg/M ³ (particulate) or oral LD ₅₀ < 10 mg/Kg (rat or mouse) <small>(see note 1 below)</small> or chemicals handled are respiratory sensitizers.
Substance handled is liquid or gaseous and it is handled in large quantities (greater than 500 milliliters) or the procedure used could release the substance to the laboratory atmosphere (heating) or you may be exposed to the substance (handling it in open containers) for an extended period of time (greater than 2 hrs. per day).	TLV or PEL >5 but < 50 ppm or substances handled are toxic to specific organ systems, carcinogens or reproductive toxins with a vapor pressure exceeding 25 mm Hg at 25°C. or oral LD ₅₀ >10 but < 500 mg/Kg (rat or mouse) <small>(see note 1 below)</small>
Substance handled is a solid and the particle size of the material is small (respirable) or consistency of the material is "light and fluffy" and the procedure used may generate airborne particulates.	TLV or PEL >0.2 but < 2 mg/M ³ or oral LD ₅₀ >10 but < 50 mg/Kg (rat or mouse) <small>(see note 1 below)</small>

Note 1: The oral LD₅₀ hood use criteria has been included because it is often the only toxicological data available on a Material Safety Data Sheet. The species of animals most often used in these acute toxicity tests are the rat and/or the mouse. The LD₅₀ criterion outlined in the table is a reasonable "rule of thumb" for materials that require control due to their acute toxicity characteristics. LD₅₀ data should only be used if other criteria are unavailable.

2.3.5.2 Eyewashes and Safety Showers

Whenever chemicals have the possibility of damaging the skin or eyes, an emergency supply of water must be available. All laboratories in which bulk quantities of hazardous chemicals are handled and could contact the eyes or skin resulting in injury should have access to eyewash stations and safety showers. As with any safety equipment, these can only be useful if they are accessible, therefore:

- Keep all passageways to the eyewash and shower clear of any obstacle (even a temporarily parked chemical cart).
- The eyewash should be checked routinely to be certain that water flows through it.
- Showers should be checked routinely to assure that access is not restricted and that the pull chain/bar is within reach.
- The flow through the safety showers should be tested periodically to ensure sufficient flow (approximately 30 gallons per minute).

The Office of Environmental Health and Safety will check eyewashes and showers twice yearly to supplement the above work, which is to be conducted by lab personnel.

2.3.5.3 Fire Safety Equipment

Fire safety equipment easily accessible in the laboratory must include a fire extinguisher (type ABC) and may include fire hoses, fire blankets, and automatic extinguishing systems.

2.4 CHEMICAL PROCUREMENT, DISTRIBUTION AND STORAGE

2.4.1 Procurement

Before a new substance that is known or suspected to be hazardous is received, information on proper handling, storage, and disposal should be known to those who will handle it. It is the responsibility of the supervisor to ensure that the laboratory facilities in which the substance will be handled are adequate and that those who will handle the substance have received the proper training. The necessary information on proper handling of hazardous substances can be obtained from the Material Safety Data Sheets that are provided by the vendor. Because storage in laboratories is restricted to small containers, order small-container lots to avoid hazards associated with repackaging. No container should be accepted without an adequate identifying label as outlined in Section 1.5.3.2 of this manual.

2.4.2 Distribution

When hand-carrying open containers of hazardous chemicals or unopened containers with corrosive or highly acutely or chronically toxic chemicals, place the container in a secondary container or a bucket. Rubberized buckets are commercially available and provide both secondary containment as well as "bump" protection. If several bottles must be moved at once, the bottles should be transported on a small cart with a substantial rim to

prevent slippage from the cart. Wherever available, a freight elevator should be used to transport chemicals from one floor to another.

2.4.3 Chemical Storage in the Laboratory

Carefully read the label before storing a hazardous chemical. The MSDS will provide any special storage information as well as information on incompatibilities. *Do not store unsegregated chemicals in alphabetical order. Do not store incompatible chemicals in close proximity to each other.*

Separate hazardous chemicals in storage as follows:

- Solids:
 - oxidizers
 - flammable solids (red phosphorus, magnesium, lithium)
 - water reactives
 - others
- Liquids:
 - acids
 - oxidizers
 - flammable/combustible
 - caustics
 - perchloric acid
- Gases:
 - toxic
 - oxidizers and inert
 - flammable

Once separated into the above hazard classes, chemicals may be stored alphabetically.

Use approved storage containers and safety cans for flammable liquids. It is preferable to store flammable chemicals in [flammable storage cabinets](#). *Flammable chemicals requiring refrigeration should be stored only in the refrigerators and freezers specifically designed for flammable storage.*

A good place to store hazardous chemicals is a vented cabinet under the hood. Chemicals of different chemical classes can be segregated by placing them in trays. Do not store chemicals on bench tops or in hoods. Liquids (particularly corrosives or solvents) should not be stored above eye level.

Use secondary containers (one inside the other) for especially hazardous chemicals (carcinogens, etc.). Use spill trays under containers of strong reagents.

Avoid exposure of chemicals while in storage to heat sources (especially open flames) and direct sunlight.

Conduct annual inventories of chemicals stored in the laboratory and dispose of old or unwanted chemicals promptly in accordance with the facility's hazardous chemical waste program.

Ensure that all containers are properly labeled.

2.4.3.1 Chemical Storage - Chemical Stability

Stability refers to the susceptibility of a chemical to dangerous decomposition. The label and MSDS will indicate if a chemical is unstable.

Special note: peroxide formers- Ethers, liquid paraffins and olefins form peroxides on exposure to air and light. Peroxides are extremely sensitive to shock, sparks, or other forms of accidental ignition (even more sensitive than primary explosives such as TNT). Since these chemicals are packaged in an air atmosphere, peroxides can form even though the containers have not been opened. Unless an inhibitor was added by the manufacturer, sealed containers of ethers should be discarded after one (1) year. Opened containers of ethers should also be discarded within one (1) year of opening. All such containers should be dated upon receipt and upon opening ([see Peroxide fact sheet](#)).

See Section 3.2, Highly Reactive Chemicals and High energy Oxidizers for additional information and examples of materials that may form explosive peroxides.

For additional information on chemical stability, contact your supervisor or the N.U. Chemical Hygiene Officer.

2.4.3.2 Chemical Storage - Incompatible Chemicals

Certain hazardous chemicals should not be mixed or stored with other chemicals because a severe reaction can take place or an extremely toxic reaction product can result. The label and MSDS will contain information on incompatibilities. The following table contains examples of incompatible chemicals:

CHEMICAL	KEEP OUT OF CONTACT WITH
Acetic Acid	Chromic acid, nitric acid hydroxyl compounds, ethylene, glycol, perchloric acid, peroxides, permanganates
Acetone	Concentrated nitric and sulfuric acid mixtures
Acetylene	Chlorine, bromine, copper, fluorine, silver, mercury
Alkali Metals	Water, carbon tetrachloride or other chlorinated hydrocarbons, carbon dioxide, the halogens

Ammonia, anhydrous	Mercury, chlorine, calcium hypochlorite, iodine, bromine, hydrofluoric acid
Ammonium Nitrate	Acids, metal powders, flammable liquids, chlorates, nitrites, sulfur, finely divided organic or combustible materials
Aniline	Nitric acid, hydrogen peroxide
Arsenical materials	Any reducing agent
Azides	Acids
Bromine	Same as chlorine
Calcium Oxide	Water
Carbon (activated)	Calcium hypochlorite, all oxidizing agents.
Carbon tetrachloride	Sodium
Chlorates	Ammonium salts, acids, metal powders, sulfur, finely divided organic or combustible materials
Chromic Acid	Acetic acid, naphthalene, camphor, glycerin, turpentine, alcohol, flammable liquids in general
Chlorine	Ammonia, acetylene, butadiene, butane, methane, propane (or other petroleum gases), hydrogen, sodium carbide, turpentine, benzene, finely divided metals
Chlorine Dioxide	Ammonia, methane, phosphine, hydrogen sulfide
Copper	Acetylene, hydrogen peroxide
Cumene Hydroperoxide	Acids, organic or inorganic
Cyanides	Acids
Flammable Liquids	Ammonium nitrate, chromic acid, hydrogen peroxide, nitric acid, sodium peroxide, halogens
Hydrocarbons	Fluorine, chlorine, bromine, chromic acid, sodium peroxide
Hydrocyanic Acid	Nitric acid, alkali

Hydrofluoric Acid	Ammonia, aqueous or anhydrous
Hydrogen Peroxide	Copper, chromium, iron, most metals or their salts, alcohols, acetone, organic materials, aniline, nitromethane, flammable liquids, oxidizing gases
Hydrogen Sulfide	Fuming nitric acid, oxidizing gases, acetylene, ammonia (aqueous or anhydrous), hydrogen
Hypochlorites	Acids, activated carbon
Iodine	Acetylene, ammonia (aqueous or anhydrous), hydrogen
Mercury	Acetylene, fulminic acid, ammonia
Nitrates	Sulfuric acid
Nitric Acid (concentrated)	Acetic acid, aniline, chromic acid, hydrocyanic acid, hydrogen sulfide, flammable liquids, flammable gases
Nitrites	Acids
Nitroparaffins	Inorganic bases, amines
Oxalic Acid	Silver, mercury
Oxygen	Oils, grease, hydrogen; flammable liquids, solids, or gases
Perchloric Acid	Acetic anhydride, bismuth and its alloys, alcohol, paper, wood
Peroxides, organic	Acids (organic or mineral), avoid friction, store cold
Phosphorus (white)	Air, oxygen, alkalies, reducing agents
Potassium	Carbon tetrachloride, carbon dioxide, water
Potassium Chlorate	Sulfuric and other acids
Potassium Permanganate	Glycerin, ethylene glycol, benzaldehyde, sulfuric acid
Selenides	Reducing agents
Silver	Acetylene, oxalic acid, tartaric acid, ammonium compounds
Sodium	Carbon tetrachloride, carbon dioxide, water
Sodium nitrite	Ammonium nitrate and other ammonium salts

Sodium Peroxide	Ethyl or methyl alcohol, glacial acetic acid, acetic anhydride, benzaldehyde, carbon disulfide, glycerin, ethylene glycol, ethyl acetate, methyl acetate, furfural
Sulfides	Acids
Sulfuric Acid	Potassium chlorate, potassium perchlorate, potassium permanganate (or compounds with similar light metals, such as sodium, lithium, etc.)
Tellurides	Reducing agents

(From Manufacturing Chemists' Association, Guide for Safety in the Chemical Laboratory, pp.215-217.)

2.5 CHEMICAL SPILLS & ACCIDENTS

2.5.1 General Information

Try to anticipate the types of chemical spills that can occur in your laboratory and obtain the necessary equipment (spill kits and personal protective equipment) to respond to a minor spill. Learn how to clean up minor spills of the chemicals you use regularly safely. A MSDS contains special spill clean-up information and should also be consulted. *Chemical spills should only be cleaned up by knowledgeable and experienced personnel.*

If the spill is too large for you to handle, is a threat to health safety or the environment, or involves a highly toxic or reactive chemical, call for assistance immediately:

The Office of Environmental Health and Safety, x2769 (8:30 a.m. to 4:30 p.m.) Division of Public Safety, x3333 (24 hours/day). A [Contingency Plan](#) is maintained by the Office of Environmental Health and Safety to handle such spills.

2.5.2 Cleaning Up Chemical Spills

If you are cleaning up a small spill yourself, make sure that you are aware of the hazards associated with the materials spilled, have adequate ventilation (open windows, chemical fume hood on) and proper personal protective equipment (minimum - gloves, goggles and lab coat). Consider all residual chemical and cleanup materials (adsorbent, gloves, etc.) as hazardous waste. Place these materials in a sealed container (plastic bags) and store in a chemical fume hood. Contact the Office of Environmental Health and Safety for disposal instructions.

2.5.3 Minor Chemical Spill

- Alert people in immediate area of spill.
- Increase ventilation in area of spill (open windows, turn on hoods).

- Wear personal protective equipment, including safety goggles, gloves and long-sleeve lab coat.
- Avoid breathing vapors from spill.
- Use appropriate kit to neutralize and absorb inorganic acids and bases. Collect residue, place in container, and dispose as hazardous chemical waste.
- For other chemicals, use appropriate kit or absorb spill with vermiculite, dry sand, diatomaceous earth or paper towels. Collect residue, place in container, and dispose as chemical waste.
- Clean spill area with water.

2.5.4 Major Chemical Spill

- Attend to injured or contaminated persons and remove them from exposure.
- Alert people in the laboratory to evacuate.
- If spilled material is flammable, turn off ignition and heat sources. Place other device (plastic bag) over spilled material to keep substance from volatilizing.
- Call **Chemical Spill Emergency Response** number x3333.
- Close doors to affected area.
- Have a person with knowledge of the incident and laboratory available to answer questions from responding emergency personnel.

2.5.5 Mercury Spills

Use a vacuum line with an in-line dry trap attached to a tapered glass tube similar to a medicine dropper to pick up mercury droplets. OEHS has a mercury vacuum and other mercury spill clean-up supplier available for laboratory personnel to use to handle mercury spills. *Do not use a domestic or commercial vacuum cleaner.*

Cover small droplets in inaccessible areas with one of the following:

- Powdered sulfur
- Powdered zinc

Place residue in a labeled container and dispose of as hazardous chemical waste.

2.5.6 Alkali Metal Spills

Smother with powdered graphite, sodium carbonate, calcium carbonate or "Met-L-X". Call the NU Chemical Hygiene Officer for assistance.

2.5.7 White Phosphorus

Smother with wet sand or wet "noncombustible" absorbent. Call the N.U. Chemical Hygiene Officer for assistance.

2.6 PERSONAL CONTAMINATION AND INJURY

2.6.1 General Information

- Know the locations of the nearest safety shower and eye wash fountain.
- Report all incidents and injuries to your supervisor.
- If an individual is contaminated or exposed to a hazardous material in your laboratory, do what is necessary to protect their life and health as well as your own. Determine what the individual was exposed to. The MSDS will contain special first aid information ([also see Cryogenic fact sheet](#)).
- Do not move an injured person unless they are in further danger (from inhalation or skin exposure).
- A blanket should be used immediately to protect the victim from shock and exposure.
- Get medical attention promptly by dialing x3333.

2.6.2 Chemicals Spills on the Body

- Quickly remove all contaminated clothing and footwear.
- Immediately flood the affected body area with cold water for at least 15 minutes. Remove jewelry to facilitate removal of any residual material.
- Wash off chemical with water only. *Do not use neutralizing chemicals, unguents, creams, lotions or salves.*
- Get medical attention promptly by dialing x3333.

It should be noted that some chemicals (phenol, aniline,) are rapidly adsorbed through the skin. If a large enough area of skin is contaminated, an adverse health effect (systemic toxicological reaction) may occur immediately to several hours after initial exposure depending on the chemical. If more than 9 square inches of skin area has been exposed to a hazardous chemical, seek medical attention after washing the material off the skin. If the incident involves [hydrofluoric acid](#), seek immediate medical attention. Provide the physician with the chemical name.

2.6.3 Chemical Splash in the Eye

- Irrigate the eyeball and inner surface of eyelid with plenty of cool water for at least 15 minutes. Use eyewash or other water source. Forcibly hold eyelids open to ensure effective wash.
- Check for and remove contact lenses.
- Get medical attention promptly.

2.6.4 Ingestion of Hazardous Chemicals

- Identify the chemical ingested.
- Call for an ambulance by dialing x3333.
- Call the Poison Information Center by dialing (800) 222-1222.
- Cover the injured person to prevent shock.

- Provide the ambulance crew and physician with the chemical name and any other relevant information. If possible, send the container, MSDS or the label with the victim.

2.6.5 Inhalation of Smoke, Vapors and Fumes

- Anyone overcome with smoke or chemical vapors or fumes should be removed to uncontaminated air and treated for shock.
- Do not enter the area if you expect that a life threatening condition still exists - oxygen depletion, explosive vapors or highly toxic gases (cyanide gas, hydrogen sulfide, nitrogen oxides, carbon monoxide)
- If CPR certified, follow standard CPR protocols.
- Get medical attention promptly.

2.6.6 Burning Chemicals on Clothing

- Extinguish burning clothing by using the drop-and-roll technique or by dousing with cold water, or use an emergency shower **if it is immediately available**.
- Remove contaminated clothing; however, avoid further damage to the burned area. If possible, send the clothing with the victim.
- Remove heat with cool water or ice packs until tissue around burn feels normal to the touch.
- Cover injured person to prevent shock.
- Get medical attention promptly.

2.6.7 Actions to be Avoided During Emergencies

There are some actions which must **not** be taken when handling emergencies. These include:

- Do not force any liquids into the mouth of an unconscious person.
- Do not handle emergencies alone, especially without notifying someone that the accident has occurred.
- Do not linger at the accident scene if you are not one of the emergency responders.

2.7 FIRE AND FIRE RELATED EMERGENCIES

If you discover a fire or fire-related emergency such as abnormal heating of material, a flammable gas leak, a flammable liquid spill, smoke, or odor of burning, immediately follow these procedures:

- Notify the Fire Department through the Division of Public Safety by dialing x3333.
- Activate the building alarm (fire pull station). If not available or operational, verbally notify people in the building.

- Isolate the area by closing windows and doors and evacuate the building.
- Shut down equipment in the immediate area, if possible.
- Use a portable fire extinguisher to:
 - assist oneself to evacuate;
 - assist another to evacuate; and
 - control a small fire, if possible.

Provide the fire/police teams with the details of the problem upon their arrival. Special hazard information you might know is essential for the safety of the emergency responders.

If the fire alarms are ringing in your building:

- You must evacuate the building and stay out until notified to return.
- Move up-wind from the building and stay clear of streets, driveways, sidewalks and other access ways to the building.
- If you are a supervisor, try to account for your employees, keep them together and report any missing persons to the emergency personnel at the scene.

2.8 HAZARDOUS WASTE DISPOSAL PROGRAM

Laboratory hazardous "chemical" waste must be disposed of in accordance with local, state, federal and Northeastern University requirements. These waste management practices are designed to ensure maintenance of a safe and healthy environment for laboratory employees and the surrounding community without adversely affecting the environment. This is accomplished through regular removal of hazardous waste and disposal of these wastes in compliance with all regulations and policies. Specific guidance on how to identify, handle, collect, segregate, store and dispose of chemical waste is available from the [hazardous waste](#) section of our Website or by contacting us directly.

Remember:

- Hazardous waste must be disposed of in a timely manner.
- Hazardous waste containers must be closed at all times during storage, except when waste is being added or removed.
- All hazardous waste must be properly labeled at the time the waste is first placed in the container.
- Hazardous waste should be accumulated in a designated storage area consistent with applicable regulations. Also, the NU [Hazardous Waste Satellite Accumulation Posting](#) must be posted at your designated storage area.
- Hazardous waste regulations require separate training of personnel who generate or handle hazardous waste.
- Do not use sinks or rubbish bins for hazardous waste disposal.
- Generators of hazardous waste are required to incorporate waste minimization into any process that generates hazardous waste.

2.9 LABORATORY CLOSEOUT PROCEDURES

Laboratories within Northeastern University must be left in a state suitable for new occupants or for renovation activities. The vacating Principal Investigator and Department are responsible for ensuring that the disposal of chemical, biological, radioactive waste materials is properly completed prior to vacating the space. In addition, the decontamination of equipment and counters must be done and arrangements made for the removal of unwanted lab equipment, electronics, and furniture. A [procedure document](#) and [check off sheet](#) have been put together to provide guidance.

SECTION 3

HEALTH AND SAFETY INFORMATION FOR WORK WITH CHEMICALS OF SPECIFIC HAZARD CLASS

3.1 FLAMMABLE LIQUIDS

3.1.1 General Information

Flammable liquids are among the most common of the hazardous materials found in laboratories. They are usually highly volatile (have high vapor pressures at room temperature) and their vapors, mixed with air at the appropriate ratio, can ignite and burn. By definition, the lowest temperature at which they can form an ignitable vapor/air mixture (the flash point) is less than 37.8 °C (100°F) and for several common laboratory solvents (ether, acetone, toluene, acetaldehyde) the flash point is well below that. As with all solvents, their vapor pressure increases with temperature and, therefore, as temperatures increase they become more hazardous.

For a fire to occur, three distinct conditions must exist simultaneously:

1. the concentration of the vapor must be between the upper and lower flammable limits of the substance (the right fuel/air mix);
2. an oxidizing atmosphere, usually air, must be available; and
3. a source of ignition must be present.

Removal of any of these three conditions will prevent the start of a fire. Flammable liquids may form flammable mixtures in either open or closed containers or spaces (such as refrigerators), when leaks or spills occur in the laboratory, and when heated.

Control strategies for preventing ignition of flammable vapors include removing all sources of ignition or maintaining the concentration of flammable vapors below the lower flammability limit by using local exhaust ventilation such as a hood. The former strategy is more difficult because of the numerous ignition sources in laboratories. Ignition sources include open flames, hot surfaces, operation of electrical equipment and static electricity.

The concentrated vapors of flammable liquids are denser than air and can travel away from a source a considerable distance (across laboratories, into hallways, down elevator shafts or stairways). If the vapors reach a source of ignition, a flame can result that may flash back to the source of the vapor.

The danger of fire and explosion presented by flammable liquids can usually be eliminated or minimized by strict observance of safe handling, dispensing and storing procedures.

3.1.2 Special Handling Procedures

While working with flammable liquids you should wear gloves, protective glasses, and a long sleeved lab coat. Wear goggles if dispensing solvents or performing an operation that could result in a splash to the face.

Large quantities of flammable liquids should be handled in a chemical fume hood or under some other type of local exhaust ventilation. Five gallon containers must be dispensed to smaller containers in a hood or under local exhaust ventilation. When dispensing flammable solvents into small storage containers, use metal or plastic containers or safety cans (avoid glass containers).

Make sure that metal surfaces or containers through which flammable substances are flowing are properly grounded, discharging static electricity. Free flowing liquids generate static electricity which can produce a spark and ignite the solvent.

Large quantities of flammable liquids must be handled in areas free of ignition sources (including spark emitting motors and equipment) using non-sparking tools. Remember that vapors are denser than air and can travel to a distant source of ignition.

Never heat flammable substances by using an open flame. Instead, use any of the following heat sources: steam baths, water baths, oil baths, heating mantles or hot air baths.

Do not distill flammable substances under reduced pressure.

Store flammable substances away from ignition sources. The preferred storage location is in flammable storage cabinets. If no flammable storage cabinet is available, store these substances in a cabinet under the hood or bench. Five gallon containers should only be stored in a flammable storage cabinet or under a hood. You can also keep the flammable liquids inside the hood for a short period of time. Storage in chemical fume hood is not preferred because it reduces hood performance by obstructing air flow.

The volume of flammable liquids dispensed in small containers (not including safety cans) in the open areas of laboratories should not exceed 10 gallons in most laboratories. Review the [Boston Fire Department restrictions on storage of flammables](#) in the Laboratory Safety section of the EHS Office homepage. Never store glass containers of flammable liquids on the floor.

Oxidizing and corrosive materials should not be stored in close proximity to flammable liquids.

Flammable liquids should not be stored or chilled in domestic refrigerators and freezers but in units specifically designed for this purpose. It is acceptable to store or chill flammable in ultra-low temperature units.

If flammable liquids will be placed in ovens, make sure they are appropriately designed for flammable liquids (no internal ignition sources and/or vented mechanically).

3.2 HIGHLY REACTIVE CHEMICALS & HIGH ENERGY OXIDIZERS

3.2.1 General Information

Highly reactive chemicals include those, which are inherently unstable and susceptible to rapid decomposition as well as chemicals that under specific conditions, can react alone, or with other substances in a violent, uncontrolled manner, liberating heat, toxic gases, or leading to an explosion. Reaction rates almost always increase dramatically as the temperature increases. Therefore, if heat evolved from a reaction is not dissipated, the reaction can accelerate out of control and possibly result in injuries or costly accidents.

Air, light, heat, mechanical shock (when struck, vibrated or otherwise agitated), water and certain catalysts can cause decomposition of some highly reactive chemicals, and initiate an explosive reaction. Hydrogen and chlorine react explosively in the presence of light. Alkali metals, such as sodium, potassium and lithium, react violently with water, liberating hydrogen gas. Examples of shock sensitive materials include acetylides, azides, organic nitrates, nitro compounds, and many peroxides.

Organic peroxides are a special class of compounds that have unusual stability problems, making them among the most hazardous substances normally handled in laboratories. As a class, organic peroxides are low powered explosives. Organic peroxides are extremely sensitive to light, heat, shock, sparks, and other forms of accidental ignition, as well as to strong oxidizing and reducing materials. All organic peroxides are highly flammable.

[Peroxide formers](#) can form peroxides during storage and especially after exposure to the air (once opened). Peroxide forming substances include aldehydes, ethers (especially cyclic ethers), compounds containing benzylic hydrogen atoms, compounds containing the allylic structure (including most alkenes), vinyl and vinylidene compounds.

Examples of shock sensitive chemicals, a high energy oxidizers and substances which can form explosive peroxides are listed at the end of this section.

3.2.2 Special Handling Procedures

Before working with a highly reactive material or a high energy oxidizer, review available reference literature to obtain specific safety information. The proposed reactions should be discussed with your supervisor. Always minimize the amount of material involved in the experiment; the smallest amount sufficient to achieve the desired result should be used. Scale-ups should be handled with great care, giving consideration to the reaction vessel size and cooling, heating, stirring and equilibration rates.

Excessive amounts of highly reactive compounds should not be purchased, synthesized, or stored in the laboratories. The key to safely handling reactive chemicals is to keep them

isolated from the substances that initiate their violent reactions. Unused peroxides should not be returned to the original container.

Do not work alone. All operations where highly reactive and explosive chemicals are used should be performed during the normal work day or when other employees are available either in the same laboratory or in the immediate area.

Perform all manipulations of highly reactive or high energy oxidizers in a chemical fume hood. (Some factors to be considered in judging the adequacy of the hood include its size in relation to the reaction and required equipment, the ability to fully close the sash, and the composition of the sash.)

Make sure that the reaction equipment is properly secured. Reaction vessels should be supported from beneath with tripods or lab jacks. Use shields or guards, which are clamped or secured.

If possible, use remote controls for controlling the reaction (including cooling, heating and stirring controls). These should be located either outside the hood or at least outside the shield.

Handle shock sensitive substances gently, avoid friction, grinding and all forms of impact. Glass containers that have screw-cap lids or glass stoppers should not be used. Polyethylene bottles that have screw-cap lids may be used. Handle water-sensitive compounds away from water sources. Light-sensitive chemicals should be used in light-tight containers. Handle highly reactive chemicals away from the direct light, open flames and other sources of heat. Oxidizing agents should only be heated with fiberglass heating mantles or sand baths.

High energy oxidizers, such as perchloric acid, should only be handled in a wash down hood if the oxidizer will volatilize and potentially condense in the ventilation system. Inorganic oxidizers such as perchloric acid can react violently with most organic materials.

When working with highly reactive compounds and high energy oxidizers, always wear the following personal protection equipment: lab coats, gloves and protective glasses/goggles. During the reaction, a face shield long enough to give throat protection should be worn.

Labels on peroxide forming substances should contain the date the container was received, first opened and the initials of the person who first opened the container. They should be checked for the presence of peroxides before using, and quarterly while in storage (peroxide test strips are available at EHS Office). If peroxides are found, the materials should be decontaminated, if possible, or disposed of. The results of any testing should be placed on the container label. Never distill substances contaminated with peroxides. Peroxide forming substances that have been opened for more than one year should be discarded. *Never use a metal spatula with peroxides. Contamination by metals can lead to explosive decompositions.*

Store highly reactive chemicals and high energy oxidizers in closed cabinets segregated from the materials with which they react and, if possible, in secondary containers. You can also store them in the cabinet under a hood. Do not store these substances above eye level or on open shelves.

Store peroxides and peroxide forming compounds at the lowest possible temperature. If you use a refrigerator, make sure it is appropriately designed for the storage of flammable substances. Store light-sensitive compounds in the light-tight containers. Store water-sensitive compounds away from water sources.

Shock sensitive materials should be discarded after one year if in a sealed container and within six months of opening unless an inhibitor was added by the manufacturer.

3.2.3 List of Shock Sensitive Chemicals

Shock sensitive refers to the susceptibility of the chemical to rapidly decompose or explode when struck, vibrated or otherwise agitated. The following are examples of materials that can be shock sensitive:

Acetylides of heavy metals	Heavy metal azides	Picramic acid
Aluminum ophrite explosive	Hexanite	Picramide
Amatol	Hexanitrodiphenylamine	Picratol
Ammonal	Hexanitrostilbene	Picric acid
Ammonium nitrate	Hexogen	Picryl chloride
Ammonium perchlorate	Hydrazinium nitrate	Picryl fluoride
Ammonium picrate	Hydrazoic acid	Polynitro aliphatic compounds
Ammonium salt lattice	Lead azide	Potassium nitroaminotetrazole
Butyl tetryl	Lead mannite	Silver acetylide
Calcium nitrate	Lead mononitroresorcinate	Silver azide
Copper acetylide	Lead picrate	Silver styphnate
Cyanuric triazide	Lead salts	Silver tetrazene
Cyclotrimethylenetrinitramine	Lead styphnate	Sodatol

Cyclotetramethylenetranitramine	Trimethylolethane	Sodium amatol
Dinitroethyleneurea	Magnesium ophorite	Sodium dinitro-orthocresolate
Dinitroglycerine	Mannitol hexanitrate	Sodium nitrate-potassium
Dinitrophenol	Mercury oxalate	Sodium picramate
Dinitrophenolates	Mercury tartrate	Styphnic acid
Dinitrophenyl hydrazine	Mononitrotoluene	Tetrazene
Dinitrotoluene	Nitrated carbohydrates	Tetranitrocarbazole
Dipicryl sulfone	Nitrated glucoside	Tetrytol
Dipicrylamine	Nitrated polyhydric alcohol	Trimonite
Erythritol tetranitrate	Nitrogen trichloride	Trinitroanisole
Fulminate of mercury	Nitrogen triiodide	Trinitrobenzene
Fulminate of silver	Nitroglycerin	Trinitrobenzoic acid
Fulminating gold	Nitroglycide	Trinitrocresol
Fulminating mercury	Nitroglycol	Trinitro- <i>meta</i> -cresol
Fulminating platinum	Nitroguanidine	Trinitronaphthalene
Fulminating silver	Nitroparaffins	Trinitrophenetol
Gelatinized nitrocellulose	Nitronium perchlorate	Trinitrophenloroglucinol
Germane	Nitrourea	Trinitroresorcinol
Guanyl nitrosamino	Organic amine nitrates	Tritonal
guanyltetrazene	Organic nitramines	Urea nitrate
Guanyl nitrosaminoguanilydene-hydrazine	Organic peroxides	

3.2.4 List of High Energy Oxidizers

The following are examples of materials that are powerful oxidizing reagents:

Ammonium permanganate	Fluorine	Potassium perchlorate
Barium peroxide	Hydrogen peroxide	Potassium peroxide
Bromine	Magnesium perchlorate	Propyl nitrate
Calcium chlorate	Nitric acid	Sodium chlorate
Calcium hypochlorite	Nitrogen peroxide	Sodium chlorite
Chlorine trifluoride	Perchloric acid	Sodium perchlorate
Chromium anhydride or chromic acid	Potassium bromate	Sodium Peroxide

3.2.5 List of Peroxide Formers

The following are examples of the materials commonly used in laboratories which may form explosive peroxides:

Acetal	Dimethyl ether	Sodium amide
Cyclohexene	Dioxane	Tetrahydrofuran
Decahydronaphthalene	Divinyl acetylene	Tetrahydronaphthalene
Diacetylene	Ether (glyme)	Vinyl ethers
Dicyclopentadiene	Ethyleneglycol dimethyl ether	Vinylidene chloride
Diethyl ether	Isopropyl ether	
Diethylene glycol	Methyl acetylene	

3.3 COMPRESSED GASES

3.3.1 General Information

Compressed gases are unique in that they represent both a physical and a potential chemical hazard (depending on the particular gas). Gases contained in cylinders may be from any of the hazard classes described in this section (flammable, reactive, corrosive, or toxic). Because of their physical state (gaseous), concentrations in the laboratory can increase instantaneously if leaks develop at the regulator or piping systems, creating the potential for a toxic chemical exposure or a fire/explosion hazard. Often there is little or no indication that leaks have or are occurring. Finally, the large amount of potential energy resulting from compression of the gas makes a compressed gas cylinder a potential rocket or fragmentation bomb if the tank or valve is physically broken.

3.3.2 Special Handling Procedures

The contents of any compressed gas cylinder should be clearly identified. No cylinder should be accepted for use that does not legibly identify its contents by name. Color coding is not a reliable means of identification and labels on caps have no value as caps are interchangeable.

Carefully read the label before using or storing a compressed gas. The MSDS will provide any special hazard information.

Transport gas cylinders in carts one or two at a time only while they are secured and capped. All gas cylinders should be capped and secured when stored. Use suitable racks, straps, chains or stands to support cylinders. All cylinders, full or empty, must be restrained and kept away from heat sources. Store as few cylinders as possible in your laboratory.

Use only Compressed Gas Association standard combinations of valves and fittings for compressed gas installations. Always use the correct pressure regulator. Do not use a regulator adaptor.

All gas lines leading from a compressed gas supply should be clearly labeled identifying the gas and the laboratory served.

Place gas cylinders in such a way that the cylinder valve is accessible at all times. The main cylinder valve should be closed as soon as the gas flow is no longer needed. Do not store gas cylinders with pressure on the regulator. Use the wrenches or other tools provided by the cylinder supplier to open a valve if available. In no case should pliers be used to open a cylinder valve.

Use soapy water to detect leaks. Leak test the regulator, piping system and other couplings after performing maintenance or modifications, which could affect the integrity of the system.

Oil or grease on the high pressure side of an oxygen cylinder can cause an explosion. Do not lubricate an oxygen regulator or use a fuel/gas regulator on an oxygen cylinder.

Never bleed a cylinder completely empty. Leave a slight pressure to keep contaminants out (172 kPa or 25 psi). Empty cylinders should not be refilled in laboratories unless they are equipped to prevent overfilling.

All gas cylinders should be clearly marked with appropriate tags indicating whether they are in use, full, or empty. Empty and full cylinders should not be stored in the same place.

Cylinders of toxic, flammable or reactive gases should be purchased in the smallest quantity possible and stored/used in a fume hood or under local exhaust ventilation. If at all possible, avoid the purchase of lecture bottles. These cylinders are not returnable and it

is extremely difficult and costly to dispose of them. Use the smallest returnable sized cylinder.

Wear safety goggles when handling compressed gases that are irritants, corrosive or toxic.

Try to purchase compressed gas cylinder that can be returned to the manufacturer (see [Management of Unwanted Compressed Gases Fact Sheet](#)).

3.3.3 Special Precautions for Hydrogen

Hydrogen gas has several unique properties which make it potentially dangerous to work with. It has an extremely wide flammability range (LEL 4%, UEL 74.5%) making it easier to ignite than most other flammable gases. Unlike most other gases, hydrogen's temperature increases during expansion. If a cylinder valve is opened too quickly, the static charge generated by the escaping gas may cause it to ignite. Hydrogen burns with an invisible flame. Caution should therefore be exercised when approaching a suspected hydrogen flame. A piece of paper can be used to tell if the hydrogen is burning. Hydrogen embrittlement can weaken carbon steel, therefore cast iron pipes and fittings must not be used. Those precautions associated with other flammable substances also apply to Hydrogen (see Section 3.1).

3.3.4 Special Precautions for Cryogenics

If not handled properly, cryogenic liquids can be hazardous to personnel. By reviewing [Cryogenics Fact Sheet](#) you will become aware of the conditions that increase the risk of accidents and injuries that can occur when working with cryogenic liquids. You will learn what can make your work place safe.

3.4 CORROSIVE CHEMICALS

3.4.1 General Information

The major classes of corrosive chemicals are strong acids and bases, dehydrating agents, and oxidizing agents. These chemicals can erode the skin and the respiratory epithelium and are particularly damaging to the eyes. Inhalation of vapors or mists of these substances can cause severe bronchial irritation. If your skin is exposed to a corrosive, flush the exposed area with water for at least fifteen minutes. Then seek medical treatment.

Strong acids. All concentrated acids can damage the skin and eyes and their burns are very painful. Nitric, chromic, and hydrofluoric acids are especially damaging because of the types of burns they inflict. Seek immediate medical treatment if you have been contaminated with these materials (particularly [hydrofluoric acid](#)). The Chemical Hygiene Committee establishes that all laboratories working with hydrofluoric (HF) acid of any concentration must have calcium gluconate and appropriate training in place in case of an exposure to this material

Strong alkalis. The common bases used in the laboratories are potassium hydroxide, sodium hydroxide and ammonia. Burns from these materials are often less painful than acids. However, damage may be more severe than acid burns because the injured person, feeling little pain, often does not take immediate action and the material is allowed to penetrate into the tissue. Ammonia is a severe bronchial irritant and should always be used in a well-ventilated area, if possible in a hood.

Dehydrating agents. This group of chemicals includes concentrated sulfuric acid, sodium hydroxide, phosphorus pentoxide and calcium oxide. Because much heat is evolved on mixing these substances with water, mixing must be done by adding the agent to water and not the reverse, to avoid violent reaction and spattering. Because of their affinity for water, these substances cause severe burns on contact with skin. Affected areas should be washed promptly with large volumes of water.

Oxidizing agents. In addition to their corrosive properties, powerful oxidizing agents such as perchloric and chromic acids (sometimes used as cleaning solutions), present fire and explosion hazards on contact with organic compounds and other oxidizable substances. The hazards associated with the use of perchloric acid are especially severe. It should be handled only after thorough familiarization with recommended operating procedures (see the section 3.2.2 on reactives & high energy oxidizers).

3.4.2 Special Handling Procedures

Corrosive chemicals should be used in the chemical fume hood and over plastic trays especially when handled in bulk quantities (> 1 liter) and when dispensing.

When working with bulk quantities of corrosives, wear gloves, face shields, laboratory coats and rubber aprons.

If you are handling bulk quantities on a regular basis, an eyewash should be immediately available and a shower close by. Spill materials - absorbent pillows, neutral absorbent materials or neutralizing materials (all commercially available) should be available in the laboratory.

Store corrosives in cabinets, under the hood or on low shelves, preferably in impervious trays to separate them physically from other groups of chemicals. Keep containers not in use in storage areas and off bench tops.

If it is necessary to move bulk quantities from one laboratory to another or from the stockroom, use a safety carrier (rubber bucket for secondary containment and protection of the container).

3.5 CHEMICALS OF HIGH ACUTE & CHRONIC TOXICITY

3.5.1 General Information

Substances that possess the characteristic of high acute toxicity can cause injury after a single or short term exposure. The immediate toxic effects to human health range from irritation to illness and death. Hydrogen cyanide, phosgene and nitrogen dioxide are examples of substances with high acute toxicity. The lethal oral doses for an average human adult of highly toxic substances range from one ounce to a few drops. **The following procedures should be used when the oral LD₅₀ of a substance in the rat or mouse is less than 50 milligrams per kilogram body weight for solid materials or non-volatile liquids and 500 mg/kg body weight for volatile liquids or gases.** Oral LD₅₀ data for the rat or mouse is listed in the substance's MSDS. The LD₅₀ toxicity test is usually the first toxicological test performed and is a good indicator of a substance's acute toxicity.

Substances that possess the characteristic of high chronic toxicity cause damage after repeated exposure or exposure over long periods of time. Health effects often do not become evident until after a long latency period - twenty to thirty years. Substances that are of high chronic toxicity may be toxic to specific organ systems - hepatotoxins, nephrotoxins, neurotoxins, toxic agents to the hematopoietic system and pulmonary tissue or carcinogens, reproductive toxins, mutagens, teratogens or sensitizers. The definition of each of these categories of toxic substances, and examples of substances, which fall into each of these different categories, can be found in Section 4 of this manual.

Specific acute and chronic toxicity information on the substances used in your laboratory can be found on these substances' MSDS. See Section 1.5.3.1 for information on how to obtain/locate MSDS's. If you have additional questions, contact the N.U. Chemical Hygiene Officer.

3.5.2 Special Handling Procedures

Avoid or minimize contact with these chemicals by any route of exposure. Protect the hands and forearms by wearing gloves and a laboratory coat. Rinse gloves with water prior to removing them.

Use these chemicals in a chemical fume hood or other appropriate containment device if the material is volatile or the procedure may generate aerosols (See guidelines for chemical fume hood use in Section 2.3.5.1). If a chemical fume hood is used, it should be evaluated to confirm that it is performing adequately (a face velocity of at least 100 linear feet per minute ($\pm 20\%$)) with the sash at the operating height.

Store volatile chemicals of high acute or chronic toxicity in the cabinet under the hood or other vented area. Volatile chemicals should be stored in unbreakable primary or secondary containers or placed in chemically resistant trays (to contain spills). Nonvolatile chemicals should be stored in cabinets or in drawers. *Do not store these chemicals on open shelves or counters.*

Decontaminate working surfaces with wet paper towels after completing procedures. Place the towels in plastic bags and secure. Confirm disposal requirements with the NU Chemical Hygiene Officer.

Volatile chemicals should be transported between laboratories in durable outer containers.

Vacuum pumps used in procedures should be protected from contamination with scrubbers or filters.

If one or more of these substances are used in large quantities, on a regular basis (three or more separate handling sessions per week) or for long periods of time (4-6 hours), a qualitative and potentially quantitative exposure assessment should be performed. Contact the N.U. Chemical Hygiene Officer to perform this assessment.

Lab personnel of childbearing age should be informed of any known male and female reproductive toxins used in the laboratory. An employee who is pregnant, or planning to become pregnant, and who is working with potential reproductive toxins that might affect the fetus, should contact the N.U. Chemical Hygiene Officer to evaluate her exposure and inform her personal physician. The N.U. Chemical Hygiene Officer can assess potential exposures and work with the employee and laboratory supervisor, if necessary, to adjust work practices to minimize the potential risk.

3.6 REGULATED CHEMICALS AND PARTICULARLY HAZARDOUS CHEMICALS

3.6.1 General Information

This section establishes supplemental work procedures to control the handling of substances that are known to exhibit unusual acute or long-term chronic health hazards (carcinogens, reproductive toxins and highly acutely toxic substances). This set of procedures applies (as indicated in Appendix A) to chemical carcinogens listed and regulated by the Department of Labor, Occupational Safety and Health Administration (OSHA), and of human carcinogens listed by the International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP).

Appendix A identifies under what conditions and for what substances the special handling procedures listed below should be used. Please note that a key component in controlling the most hazardous substances is the controlled distribution and use of these substances. In some instances special authorization is required before purchasing and using these substances.

Appendix A lists the substances and/or procedures that require prior approval of the research protocol before beginning work. See Section 1.11 for the chemical safety protocol review process.

3.6.2 Special Handling Procedures

Use these chemicals only in a chemical fume hood or other appropriate containment device (glove box). If a chemical fume hood is used, it should be evaluated to confirm that it is

performing adequately (a face velocity of at least 100 linear feet per minute with the sash at the operating height).

Volatile chemicals should be stored in a vented storage area in an unbreakable, primary or secondary container or placed in a chemically resistant tray (to contain spills). Nonvolatile chemicals should be stored in cabinets or in drawers. *Do not store these chemicals on open shelves or counters.* Access to all of these chemicals should be restricted.

Volatile chemicals should be transported between laboratories in durable outer containers.

All procedures with these chemicals should be performed in designated areas. Other employees working in the area should be informed of the particular hazards associated with these substances and the appropriate precautions that are necessary for preventing exposures. All designated areas should be posted with a sign which reads:

WARNING
DESIGNATED AREA FOR HANDLING THE FOLLOWING
SUBSTANCES WITH HIGH ACUTE OR CHRONIC TOXICITY:
[list of substances - identify acute or chronic hazard]
[Example: Benzene - carcinogen]
AUTHORIZED PERSONNEL ONLY

Vacuum pumps used in procedures should be protected from contamination with scrubbers or filters.

Analytical instruments or other laboratory equipment generating vapors and/or aerosols during their operation, should be locally exhausted or vented in a chemical fume hood.

Skin surfaces that might be exposed to these substances during routine operations or foreseeable accidents should be covered with appropriate protective clothing. Gloves should be worn whenever transferring or handling these substances. Consider using full body protection (disposable coveralls) if the potential for extensive personal contamination exists.

All protective equipment should be removed when leaving the designated area and decontaminated (washed) or, if disposable, placed in a plastic bag and secured. Call the N.U. Chemical Hygiene Officer for disposal instructions. Skin surfaces - hands, forearms, face and neck - should be washed immediately.

Work surfaces on which these substances will be handled should be covered with an easily decontaminated surface (such as stainless steel) or protected from contamination with plastic trays or plastic backed paper. Call the N.U. Chemical Hygiene Officer for decontamination and disposal procedures; these will be substance specific. Materials that will be disposed of should be placed in plastic bags and secured.

Chemical wastes from procedures using these substances should be placed in containers and disposed of as hazardous chemical waste. The wastes should be stored in the designated area (defined above) until picked up. If it is possible to safely chemically decontaminate all toxic substances to nontoxic materials during or at the end of the procedure, this should be done.

Normal laboratory work should not be conducted in a designated area until it has been decontaminated or determined to be acceptable by the principal investigator or N.U. Chemical Hygiene Officer.

If one or more of these substances are used in large quantities, on a regular basis (three or more separate handling sessions per week), or for long periods of time (4-6 hours), a qualitative and potentially quantitative exposure assessment should be performed. Contact the N.U. Chemical Hygiene Officer to have this assessment performed. The N.U. Chemical Hygiene Officer in conjunction with a Lane Health Center Physician will determine if it is appropriate to establish an ongoing medical surveillance program.

Laboratory personnel of childbearing age should be informed of any known male and female reproductive toxins used in the laboratory. An employee who is pregnant, or planning to become pregnant, and who is working with potential reproductive toxins that might affect the fetus, should contact the N.U. Chemical Hygiene Officer to evaluate her exposure and inform her personal physician. The N.U. Chemical Hygiene Officer can assess potential exposures and work with the employee and laboratory supervisor, if necessary, to adjust work practices to minimize the potential risk.

SECTION 4

CHEMICAL TOXICOLOGY

4.1 CHEMICAL TOXICOLOGY OVERVIEW

4.1.1 Definitions

Toxicology is the study of the nature and action of poisons.

Toxicity is the ability of a chemical substance or compound to produce injury once it reaches a susceptible site in, or on, the body.

A material's **hazard potential** is the probability that injury will occur after consideration of the conditions under which the substance is used.

4.1.2 Dose-Response Relationships

The potential toxicity (harmful action) inherent in a substance is exhibited only when that substance comes in contact with a living biological system. The potential toxic effect increases as the exposure increases. All chemicals will exhibit a toxic effect given a large enough dose. The toxic potency of a chemical is thus ultimately defined by the dose (the amount) of the chemical that will produce a specific response in a specific biological system.

4.1.3 Routes of Entry into the Body

There are three main routes by which hazardous chemicals enter the body:

- Absorption through the **respiratory tract** via inhalation.
- Absorption through the **skin** via dermal contact.
- Absorption through the **digestive tract** via ingestion. (Ingestion can occur through eating, drinking or smoking with contaminated hands or in contaminated work areas.)

Most exposure standards, such as the Threshold Limit Values (**TLV's**) and Permissible Exposure Limits (**PEL's**), are based on the inhalation route of exposure. These limits are normally expressed in terms of either parts per million (ppm) or milligrams per cubic meter (mg/m³) concentration in air. If a significant route of exposure to a substance is through skin contact, the MSDS, PEL and/or TLV will have a "skin" notation. Examples of substances where skin absorption may be a significant factor include: pesticides, carbon

disulfide, carbon tetrachloride, dioxane, mercury, thallium compounds, xylene and hydrogen cyanide.

4.1.4 Types of Effects

Acute poisoning is characterized by sudden and severe exposure and rapid absorption of the substance. Normally, a single large exposure is involved. Adverse health effects are sometimes reversible. Examples: carbon monoxide or cyanide poisoning.

Chronic poisoning is characterized by prolonged or repeated exposures of a duration measured in days, months or years. Symptoms may not be immediately apparent. Health effects are often irreversible. Examples: lead or mercury poisoning.

A **Local** effect refers to an adverse health effect that takes place at the point or area of contact. The site may be skin, mucous membranes, the respiratory tract, gastrointestinal system, eyes, etc. Absorption does not necessarily occur. Examples: strong acids or alkalis.

A **Systemic** effect refers to an adverse health effect that takes place at a location distant from the body's initial point of contact and presupposes absorption has taken place. Examples: arsenic affects the blood, nervous system, liver, kidneys and skin; benzene affects bone marrow.

Cumulative poisons are characterized by materials that tend to build up in the body as a result of numerous chronic exposures. The effects are not seen until a critical body burden is reached. Example: heavy metals.

Substances in combination: When two or more hazardous materials are present at the same time, the resulting effect can be greater than the effect predicted based on the additive effect of the individual substances. This is called a **synergistic** or **potentiating effect**. Example: exposure to alcohol and chlorinated solvents; or smoking and asbestos.

4.1.5 Other Factors Affecting Toxicity

Rate of entry and route of exposure; that is, how fast is the toxic dose delivered and by what means.

Age can effect the capacity to repair tissue damage.

Previous exposure can lead to tolerance, increased sensitivity or make no difference.

State of health, physical condition and life style can affect the toxic response. *Pre-existing disease* can result in increased sensitivity.

Environmental factors such as temperature and pressure.

Host factors including *genetic predisposition* and the *sex* of the exposed individual.

4.1.6 Physical Classifications

Gas applies to a substance, which is in the gaseous state at room temperature and pressure.

A **Vapor** is the gaseous phase of a material, which is ordinarily a solid or a liquid at room temperature and pressure.

When considering the toxicity of gases and vapors, the solubility of the substance is a key factor. Highly soluble materials, like ammonia, irritate the upper respiratory tract. On the other hand, relatively insoluble materials, like nitrogen dioxide, penetrate deep into the lung. Fat soluble materials, like pesticides, tend to have longer residence times in the body and be cumulative poisons.

An **aerosol** is composed of solid or liquid particles of microscopic size dispersed in a gaseous medium.

The toxic potential of an aerosol is only partially described by its airborne concentration. For a proper assessment of the toxic hazard, the size of the aerosol's particles must be determined. A particle's size will determine if a particle will be deposited within the respiratory system and the location of deposition. Particles above 10 micrometers tend to deposit in the nose and other areas of the upper respiratory tract. Below 10 micrometers particles enter and are deposited in the lung. Very small particles (<0.2 micrometers) are generally not deposited but exhaled.

4.1.7 Physiological Classifications

Irritants are materials that cause inflammation of mucous membranes with which they come in contact. Inflammation of tissue results from exposure to concentrations far below those needed to cause corrosion. Examples include:

- Ammonia
- Alkaline dusts and mists
- Hydrogen chloride
- Hydrogen fluoride
- Halogens
- Ozone
- Phosgene
- Diethyl/dimethyl sulfate
- Nitrogen dioxide
- Phosphorus chlorides
- Arsenic trichloride

Irritants can also cause changes in the mechanics of respiration and lung function. Examples include:

- Sulfur dioxide - Acetic acid
- Formaldehyde - Formic acid
- Sulfuric acid - Acrolein
- Iodine

Long term exposure to irritants can result in increased mucous secretions and chronic bronchitis.

A **primary irritant** exerts no systemic toxic action either because the products formed on the tissue of the respiratory tract are non-toxic or because the irritant action is far in excess of any systemic toxic action. Example: hydrogen chloride.

A **secondary irritant's** effect on mucous membranes is overshadowed by a systemic effect resulting from absorption. Examples include:

- Hydrogen sulfide - Aromatic hydrocarbons

Asphyxiants have the ability to deprive tissue of oxygen.

Simple asphyxiants are inert gases that displace oxygen. Examples include:

- Nitrogen - Nitrous oxide
- Carbon dioxide - Hydrogen
- Helium

Chemical asphyxiants reduce the body's ability to absorb, transport, or utilize inhaled oxygen. They are often active at very low concentrations (a few ppm). Examples include:

- Carbon monoxide - Cyanides

Primary anesthetics have a depressant effect upon the central nervous system, particularly the brain. Examples include:

- Halogenated hydrocarbons - Alcohols

Hepatotoxic agents cause damage to the liver. Examples include:

- Carbon tetrachloride
- Tetrachloroethane
- Nitrosamines

Nephrotoxic agents damage the kidneys. Examples include:

- Halogenated hydrocarbons
- Uranium compounds

Neurotoxic agents damage the nervous system. The nervous system is especially sensitive to organometallic compounds and certain sulfide compounds. Examples include:

- Trialkyl tin compounds
- Tetraethyl lead
- Methyl mercury
- Carbon disulfide
- Organic phosphorus insecticides
- Thallium
- Manganese

Some toxic agents act on the **blood or hematopoietic system**. The blood cells can be affected directly or the bone marrow (which produces the blood cells) can be damaged. Examples include:

- Nitrites
- Aniline
- Toluidine
- Nitrobenzene
- Benzene

There are toxic agents that produce damage of the **pulmonary tissue** (lungs) but not by immediate irritant action. Fibrotic changes can be caused by free silica and asbestos. Other dusts can cause a restrictive disease called **pneumoconiosis**. Examples include:

- Coal dust
- Cotton dust
- Wood dust

A **carcinogen** is an agent that can initiate or increase the proliferation of malignant neoplastic cells or the development of malignant or potentially malignant tumors. Known human carcinogens include:

- Asbestos
- 4-nitrobiphenyl
- Alpha-naphthylamine
- Methyl chloromethyl ether
- 3,3'-Dichlorobenzidine
- Bis-chloromethyl ether

- Vinyl chloride
- Ethylene oxide
- N-nitrosodimethylamine
- Inorganic arsenic
- 1,2-Dibromo-3-chloropropane (DBCP)
- Coal tar pitch volatiles

A **mutagen** interferes with the proper replication of genetic material (chromosome strands) in exposed cells. If germ cells are involved, the effect may be inherited and become part of the genetic pool passed onto future generations.

A **teratogen** (embryotoxic or fetotoxic agent) is an agent, which interferes with normal embryonic development without causing a lethal effect to the fetus or damage to the mother. Effects are not inherited. Examples include:

- Lead
- Thalidomide

A **sensitizer** is a chemical, which can cause an allergic reaction in normal tissue after repeated exposure to the chemical. The reaction may be as mild as a rash (allergic dermatitis) or as serious as anaphylactic shock. Examples include:

- Epoxies
- Nickel compounds
- Poison ivy
- Toluene diisocyanate
- Chromium compounds
- Chlorinated hydrocarbons

4.2 SOME TARGET ORGAN EFFECTS

The following is a categorization of target organ effects that may occur from chemical exposure. Signs and symptoms of these effects and examples of chemicals which have been found to cause such effects are listed.

Toxins	Target organ effect	Signs and symptoms	Example chemicals
Hepatotoxins	Cause liver damage	Jaudice; liver enlargement	Nitrosamines, chloroform, toluene, perchloroethylene, cresol, dimethylsulfate
Nephrotoxins	Cause kidney damage	Edema; proteinuria	Halogenated hydrocarbons, uranium, chloroform, mercury, dimethylsulfate

Neurotoxins	Affect the nervous system	Narcosis; behavior changes; decreased muscle coordination	Mercury, carbon disulfide, benzene, carbon tetrachloride, lead, mercury, nitrobenzene
Hematopoietic toxins	Decrease blood function	Cyanosis; loss of consciousness	Carbon monoxide, cyanides, nitrobenzene, aniline, arsenic, benzene, toluene
Pulmonary toxins	Irritate or damage the lungs	Cough; tightness in chest, shortness of breath	Silica, asbestos, ozone, hydrogen sulfide, chromium, nickel, alcohols
Reproductive toxins	Affect the reproductive system	Birth defects; sterility	Lead, dibromodichloropropane
Skin hazards	Affect the dermal layer of the body	Defatting of skin; rashes; irritation	Ketones, chlorinated compounds, alcohols, nickel, phenol, trichloroethylene
Eye hazards	Affect the eye or vision	Conjunctivitis, corneal damage	Organic solvents, acids, cresol, quinones, hydroquinone, benzyl, chloride, butyl alcohol, bases

4.3 OCCUPATIONAL HEALTH STANDARDS

TLV: The **threshold limit value** is a recommended occupational exposure guideline published by the American Conference of Governmental Industrial Hygienists. TLV's are expressed as parts of vapor or gas per million parts of air by volume (ppm) or as approximate milligrams of particulate per cubic meter of air (mg/M^3). The TLV is the average concentration of a chemical that most people can be exposed to for a working lifetime with no ill effects. The TLV is an advisory guideline. If applicable, a **ceiling concentration (C)** that should not be exceeded or a skin absorption notation (S) will be indicated with the TLV.

PEL: The **permissible exposure limit** is a legal standard issued by OSHA. Unless specified, the PEL is a time weighted average (**TWA**).

TWA: Most exposure standards are based on **time weighted averages**. The TWA is the average exposure over an eight (8) hour work day. Some substances have Ceiling (C) limits. Ceiling limits are concentrations that should never be exceeded.

The MSDS will list the occupational health standard(s) for the hazardous chemical or each component of a mixture.

SECTION 5

GLOSSARY OF TERMS

ACGIH - The American Conference of Governmental Industrial Hygienists is a voluntary membership organization of professional industrial hygiene personnel in governmental or educational institutions. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLV's) for hundreds of chemicals, physical agents, and biological exposure indices.

ACUTE - Short duration, rapidly changing conditions.

ACUTE EXPOSURE - An intense exposure over a relatively short period of time.

ANSI - The American National Standards Institute is a voluntary membership organization (run with private funding) that develops consensus standards nationally for a wide variety of devices and procedures.

ASPHYXIANT - A chemical (gas or vapor) that can cause death or unconsciousness by suffocation. Simple asphyxiants, such as nitrogen, either remove or displace oxygen in the air. They become especially dangerous in confined or enclosed spaces. Chemical asphyxiants, such as carbon monoxide and hydrogen sulfide, interfere with the body's ability to absorb or transport oxygen to the tissues.

BOILING POINT - The temperature at which the vapor pressure of a liquid equals atmospheric pressure or at which the liquid changes to a vapor. The boiling point is usually expressed in degrees Fahrenheit. If a flammable material has a low boiling point, it indicates a special fire hazard.

"C" OR CEILING - A description usually seen in connection with ACGIH exposure limits. It refers to the concentration that should not be exceeded, even for an instant. It may be written as TLV-C or Threshold Limit Value-Ceiling. (See also **THRESHOLD LIMIT VALUE**).

CARCINOGEN - A substance or physical agent that may cause cancer in animals or humans.

C.A.S. NUMBER - Identifies a particular chemical by the Chemical Abstracts Service, a service of the American Chemical Society that indexes and compiles abstracts of worldwide chemical literature called Chemical Abstracts.

cc - Cubic centimeter, a volumetric measurement which is also equal to one milliliter (ml).

CHEMICAL - As broadly applied to the chemical industry, an element or a compound produced by chemical reactions on a large scale for either direct industrial and consumer use or for reaction with other chemicals.

CHEMICAL REACTION - A change in the arrangement of atoms or molecules to yield substances of different composition and properties. (see REACTIVITY)

CHRONIC - Persistent, prolonged or repeated conditions.

CHRONIC EXPOSURE - A prolonged exposure occurring over a period of days, weeks, or years.

COMBUSTIBLE - According to the DOT and NFPA, combustible liquids are those having a flash point at or above 100°F (37.8°C), or liquids that will burn. They do not ignite as easily as flammable liquids. However, combustible liquids can be ignited under certain circumstances, and must be handled with caution. Substances such as wood, paper, etc., are termed "Ordinary Combustibles".

CONCENTRATION - The relative amount of a material in combination with another material. For example, 5 parts of (acetone) per million (parts of air).

CORROSIVE - A substance that, according to the DOT, causes visible destruction or permanent changes in human skin tissue at the site of contact or is highly corrosive to steel.

CUBIC METER (m³) - A measure of volume in the metric system.

CUTANEOUS - Pertaining to or affecting the skin.

DECOMPOSITION - The breakdown of a chemical or substance into different parts or simpler compounds. Decomposition can occur due to heat, chemical reaction, decay, etc.

DERMAL - Pertaining to or affecting the skin.

DERMATITIS - An inflammation of the skin.

DILUTION VENTILATION - See **GENERAL VENTILATION**.

DOT - The United States Department of Transportation is the federal agency that regulates the labeling and transportation of hazardous materials.

DYSPNEA - Shortness of breath; difficult or labored breathing.

EHS - Environmental Health and Safety Office.

EPA - The Environmental Protection Agency is the governmental agency responsible for administration of laws to control and/or reduce pollution of air, water, and land systems.

EPA NUMBER - The number assigned to chemicals regulated by the Environmental Protection Agency (EPA).

EPIDEMIOLOGY - The study of disease in human populations.

ERYTHEMA - A reddening of the skin.

EVAPORATION RATE - The rate at which a material is converted to vapor (evaporates) at a given temperature and pressure when compared to the evaporation rate of a given substance. Health and fire hazard evaluations of materials involve consideration of evaporation rates as one aspect of the evaluation.

°F - Degrees, Fahrenheit; a temperature scale.

FLAMMABLE LIQUID - According to the DOT and NFPA, a flammable liquid is one that has a flash point below 100°F. (See FLASH POINT)

Classes Of Flammable Liquids		
Flammable Solvent Class	Boiling Point	Flash Point
Class 1A	< 100°F	< 73°F
Class 1B	>= 100°F	< 73°F
Class 1C	>= 100°F	Between 73 and 100°F

FLASH POINT - The lowest temperature at which a liquid or a solid emits vapor sufficient to form an ignitable mixture with air near the surface of the liquid or the solid, and burn when a source of ignition (sparks, open flames, cigarettes, etc.) is present. Two tests are used to determine the flash point: open cup and closed cup. The test method is indicated on the MSDS after the flash point.

g - See GRAM.

GENERAL VENTILATION - Also known as general exhaust ventilation, this is a system of ventilation consisting of either natural or mechanically induced fresh air movements to mix with and dilute contaminants in the workroom air. This is not the recommended type of ventilation to control contaminants that are highly toxic, when there may be corrosion problems from the contaminant, when the worker is close to where the contaminant is being generated, and where fire or explosion hazards are generated close to sources of ignition (See LOCAL EXHAUST VENTILATION).

g/Kg - See GRAMS PER KILOGRAM.

GRAM (g) - A metric unit of weight. One ounce equals 28.4 grams.

GRAMS PER KILOGRAM (g/Kg) - This indicates the dose of a substance given to test animals in toxicity studies. For example, a dose may be 2 grams (of substance) per kilogram of body weight (of the experimental animal).

HAZARDOUS MATERIAL - Any substance or compound that has the capability of producing adverse effects on the health and safety of humans.

IGNITABLE - A solid, liquid or compressed gas that has a flash point of less than 140°F. Ignitable material may be regulated by the EPA as a hazardous waste, as well.

INCOMPATIBLE - The term applied to two substances to indicate that one material cannot be mixed with the other without the possibility of a dangerous reaction.

INGESTION - Taking a substance into the body through the mouth, such as food, drink, medicine, or unknowingly as in contaminated hands or cigarettes, etc.

INHALATION - Breathing in of an airborne substance that may be in the form of gases, fumes, mists, vapors, dusts, or aerosols.

INHIBITOR - A substance that is added to another to prevent or slow down an unwanted reaction or change.

IRRITANT - A substance that produces an irritating effect when it contacts skin, eyes, nose, or respiratory system.

Kg - See KILOGRAM.

KILOGRAM (Kg) - A unit of weight in the metric system equal to 2.2 pounds.

L - See LITER.

LC₅₀- See LETHAL CONCENTRATION₅₀.

LD₅₀- See LETHAL DOSE₅₀.

LEL - See LOWER EXPLOSIVE LIMIT.

LETHAL CONCENTRATION₅₀ - The concentration of an air contaminant (**LC₅₀**) that will kill 50 percent of the test animals in a group during a single exposure.

LETHAL DOSE₅₀ - The dose of a substance or chemical that will (**LD₅₀**) kill 50 percent of the test animals in a group within the first 30 days following exposure.

LFL - See LOWER EXPLOSIVE LIMIT.

LITER (L) - A measure of capacity. One quart equals 0.9 liters.

LOCAL EXHAUST VENTILATION - (Also known as exhaust ventilation.) A ventilation system that captures and removes the contaminants at the point where they are being produced before they escape into the workroom air. The system consists of hoods, ducts, a fan and possibly an air cleaning device. Advantages of local exhaust ventilation over general ventilation include: it removes the contaminant rather than dilutes it; it requires less air flow and thus is more economical over the long term; and the system can be used to conserve or reclaim valuable materials. However, the system must be properly designed with the correctly shaped and placed hoods, and correctly sized fans and duct work.

LOWER EXPLOSIVE LIMIT (LEL) - (Also known as Lower Flammable Limit). The lowest concentration of a substance that will produce a fire or flash when an ignition source (flame, spark, etc.) is present. It is expressed in percent of vapor or gas in the air by volume. Below the LEL or LFL, the air/contaminant mixture is theoretically too "lean" to burn. (See also UEL).

m³ - See CUBIC METER.

MELTING POINT - The temperature at which a solid changes to a liquid. A melting range may be given for mixtures.

mg - See MILLIGRAM.

mg/Kg - See MILLIGRAMS PER KILOGRAM.

mg/m³ - See MILLIGRAMS PER CUBIC METER.

MILLIGRAM (mg) - A unit of weight in the metric system. One thousand milligrams equal one gram.

MILLIGRAMS PER CUBIC METER - Units used to measure air (**mg/m³**) concentrations of dusts, gases, mists, and fumes.

MILLIGRAMS PER KILOGRAM - This indicates the dose of a substance (**mg/kg**) given to test animals in toxicity studies. For example, a dose may be 2 milligrams (of substance) per kilogram of body weight (of the experimental animal).

MILLILITER (ml) - A metric unit used to measure volume. One milliliter equals one cubic centimeter. One thousand milliliters equal one liter.

ml - See MILLILITER.

MSHA - The Mine Safety and Health Administration; a federal agency that regulates the mining industry in the safety and health area.

MUTAGEN - Anything that can cause a change (or mutation) in the genetic material of a living cell.

NARCOSIS - Stupor or unconsciousness caused by exposure to a chemical.

NFPA - The National Fire Protection Association is a voluntary membership organization whose aims are to promote and improve fire protection and prevention. NFPA has published 16 volumes of codes known as the National Fire Codes. Within these codes is Standard No. 704, [NFPA Hazard Rating System](#). This is a system that rates the hazard of a material during a fire. These hazards are divided into health, flammability and reactivity hazards and appear in a well-known diamond system using from zero through four to indicate severity of the hazard. Zero indicates no special hazard and four indicates severe hazard.

NIOSH - The National Institute of Occupational Safety and Health is a federal agency that among its various responsibilities trains occupational health and safety professionals, conducts research on health and safety concerns, and tests and certifies respirators for workplace use.

NU - Northeastern University.

ODOR THRESHOLD - The minimum concentration of a substance at which a majority of test subjects can detect and identify the substance's characteristic odor.

ORAL - Having to do with the mouth.

OSHA - The Occupational Safety and Health Administration - a federal agency under the Department of Labor that publishes and enforces safety and health regulations for most businesses and industries in the United States.

OXIDATION - The process of combining oxygen with some other substance to a chemical change in which an atom loses electrons.

OXIDIZER - Is a substance that gives up oxygen easily to stimulate combustion of organic material.

OXYGEN DEFICIENCY - An atmosphere having less than the normal percentage of oxygen found in normal air. Normal air contains 21% v/v oxygen at sea level.

PEL - See PERMISSIBLE EXPOSURE LIMIT.

PERMISSIBLE EXPOSURE LIMIT (PEL) - An exposure limit that is published and enforced by OSHA as a legal standard. PEL may be either a time-weighted-average (TWA) exposure limit (8 hour), a 15-minute short term exposure limit (STEL), or a ceiling (C). The PEL's are found in Tables Z-1, Z-2, or Z-3 of OSHA regulations 1910.1000. (See also TLV).

PERSONAL PROTECTIVE EQUIPMENT (PPE) - Any devices or clothing worn by the worker to protect against hazards in the environment. Examples are respirators, gloves, and chemical splash goggles.

POLYMERIZATION- A chemical reaction in which two or more small molecules combine to form larger molecules that contain repeating structural units of the original molecules. A hazardous polymerization is the above reaction with an uncontrolled release of energy.

ppm - Parts (of vapor or gas) per million (parts of air) by volume.

REACTIVITY - A substance's susceptibility to undergo a chemical reaction or change that may result in dangerous side effects, such as explosions, burning and corrosive or toxic emissions. The conditions that cause the reaction, such as heat, other chemicals and dropping, will usually be specified as "Conditions to Avoid" when a chemical's reactivity is discussed on a MSDS.

RESPIRATOR - A device that is designed to protect the wearer from inhaling harmful contaminants.

RESPIRATORY HAZARD - A particular concentration of an airborne contaminant that, when it enters the body by way of the respiratory system or by being breathed into the lungs, results in some bodily function impairment.

SENSITIZER - A substance that may cause no reaction in a person during initial exposures, but afterwards, further exposures will cause an allergic response to the substance.

SHORT TERM EXPOSURE LIMIT - Represented as STEL or TLV-STEL, this is the maximum concentration to which workers can be exposed for a short period of time (15 minutes) for only four times throughout the day with at least one hour between exposures. Also the daily TLV-TWA must not be exceeded.

"SKIN" - This designation sometimes appears alongside a TLV or PEL. It refers to the possibility of absorption of the particular chemical through the skin and eyes. Thus, protection of large surface areas of skin should be considered to prevent skin absorption so that the TLV is not invalidated.

STEL - Short Term Exposure Limit.

SUBSTANCE - Any chemical entity.

SYNONYM - Another name by which the same chemical may be known.

SYSTEMIC - Spread throughout the body; affecting many or all body systems or organs; not localized in one spot or area.

TERATOGEN - An agent or substance that may cause physical defects in the developing embryo or fetus when a pregnant female is exposed to that substance.

THRESHOLD LIMIT VALUE - Airborne concentrations of substances devised by the ACGIH that represent conditions under which it is believed that nearly all workers may be exposed day after day with no adverse effect. TLV's are advisory exposure guidelines, not legal standards, that are based on evidence from industrial experience, animal studies, or human studies when they exist. There are three different types of TLV's: Time Weighted Average (TLV-TWA), Short Term Exposure Limit (TLV-STEL) and Ceiling (TLV-C). (See also PEL.)

TIME WEIGHTED AVERAGE - The average time, over a given work period (e.g., 8-hour work day), of a person's exposure to a chemical or an agent. The average is determined by sampling for the contaminant throughout the time period. Represented as TLV-TWA.

TLV - See THRESHOLD LIMIT VALUE.

TOXICITY - The potential for a substance to exert a harmful effect on humans or animals and a description of the effect and the conditions or concentrations under which the effect takes place.

TRADE NAME - The commercial name or trademark by which a chemical is known. One chemical may have a variety of trade names depending on the manufacturers or distributors involved.

TWA - See TIME WEIGHTED AVERAGE.

UEL - See UPPER EXPLOSIVE LIMIT.

UFL - See UPPER EXPLOSIVE LIMIT.

UNSTABLE LIQUID - A liquid that, in its pure state or as commercially produced, will react vigorously in some hazardous way under shock conditions (e.g., dropping), certain temperatures, or pressures.

UPPER EXPLOSIVE LIMIT - Also known as Upper Flammable Limit. Is the highest concentration (expressed in percent of vapor or gas in the air by volume) of a substance that will burn or explode when an ignition source is present. Theoretically, above this limit the mixture is said to be too "rich" to support combustion. The difference between the LEL and the UEL constitutes the flammable range or explosive range of a substance. That is, if the LEL is 1ppm and the UEL is 5ppm, then the explosive range of the chemical is 1ppm to 5ppm. (see also LEL).

VAPOR - The gaseous form of substances that are normally in the liquid or solid state (at normal room temperature and pressure). Vapors evaporate into the air from liquids such as solvents. Solvents with low boiling points will evaporate.

Appendix A

Laboratory Chemical Hygiene Plan

Appendix A

Chemicals Requiring Prior Approval

I. Acutely Toxic Gases

The pressurized hazardous gases identified below have been classified as particularly hazardous and *require prior approval for purchasing of new materials, or handling and storage of existing material*. See Section 1.11, Research Protocol Review, for the approval procedure.

Pressurized Gases Requiring Review

Compound	Exempt Quantity
Arsine and gaseous derivatives	None
Chloropicrin in gas mixtures	None
Cyanogen chloride	None
Cyanogen	None
Diborane	None
Germane	None
Hexaethyltetraphosphate	None
Hydrogen cyanide	None
Hydrogen selenide	None
Nitric oxide	None
Nitrogen dioxide	None
Nitrogen Tetroxide	None
Phosgene	None
Phosphine	None

II. Regulated Chemicals & Chemicals with High Chronic Toxicity

The substances listed in the table below (titled "Regulated Chemicals & Chemicals with High Chronic Toxicity Requiring Special Procedures") when stored or handled in quantities exceeding the exempt quantities must be stored and handled according to the special procedures outlined in Section 3.6.2. If it is not possible to utilize these procedures the proposed alternative procedures must be reviewed and approved by the NU Chemical Hygiene Officer prior to initiating the research. See Section 1.11, Research Protocol Review, for the approval procedure. If you are using any of these substances in quantities

less than the exempt amount, use the procedures outlined in Section 3.5.2, Chemicals of High Acute or Chronic Toxicity.

Compound	Exempt Quantity ^(See Note 1 Below)	OSHA Regulated Substance
N-Acetoxy-2-acetylaminofluorene	2	
2-Acetylaminofluorene	2	Y
Acrylonitrile	1	Y
Aflatoxins	2	
o-Aminoazotoluene	2	
4-Aminodiphenyl	3	Y
2-Aminofluorene	2	
Asbestos	1	Y
Arsenic and arsenic compounds	2	Y
Azathiopurine	2	
Benz[a]anthracene	2	
Benzene	1	Y
Benzidine	3	Y
Benzo[a]pyrene	2	
Bromoethyl methanesulfonate	2	
1,4-Butanediol dimethanesulfonate (myleran)	2	
Carbon tetrachloride	1	
Chlorambucil	2	
Chloroform	1	
N,N-bis(2-chloroethyl)-2-naphthylamine	2	
bis-Chloromethyl ether	3	Y
1-(2-Chloroethyl)-3-(4-methylcyclohexyl)-1-nitrosourea	2	
Cycasin	2	
Cyclophosphamide	2	
Diazomethane	2	
Dibenz[a,h]anthracene	2	
1,2-Dibromo-3-chloropropane	1	Y
3,3'-Dichlorobenzidine (& its salts)	3	Y
Diepoxybutane	2	
4-Dimethylaminoazobenzene	2	Y
7,12-Dimethylbenz[a]anthracene	2	
3,3'-Dimethylbenzidine	2	

1,1-Dimethylethylenimine	1	
1,1-Dimethylhydrazine	2	
1,2-Dimethylhydrazine	2	
1,4-Dinitrosopiperazine	2	
p-Dioxane	1	
Ethylene dibromide	1	
Ethyleneimide	2	Y
Ethyl methanesulfonate	2	
Ethylene oxide	1	Y
Ethionine	1	
Ethylenimine	2	
Formaldehyde	1	Y
Hexavalent chromium and chromium compounds	1	
Hydrazine	2	
N-Hydroxy-2-acetylaminofluorene	2	
Lead and lead compounds	1	Y
Mercury and Mercury salts	3	Y
3'-Methyl-4-aminoazobenzene	1	
Methyl chloromethyl ether	3	
3-Methylcholanthrene	2	
4,4'-Methylene bis(2-chloroaniline)	2	
Methylhydrazine	2	
Methyl mercury	3	
Methyl methanesulfonate	2	
1-Methyl-3-nitro-1-nitrosoguanidine	2	
alpha-Naphthylamine	2	Y
beta-Naphthylamine	3	Y
4-Nitrobiphenyl	3	Y
N-[4-(5-nitro-2-furyl)-2-thiazoyl]-formamide	2	
4-Nitroquinoline-1-oxide	2	
N-Nitrosodiethylamine	2	
N-Nitrosodimethylamine	2	Y
N-Nitrosodi-n-butylamine	2	
N-Nitrosodi-n-propylamine	2	
N-Nitroso-N-ethylurea	2	
N-Nitroso-N-ethylurethane	2	

N-Nitroso-N-methylurea	2	
N-Nitroso-N-methylurethane	2	
N-Nitrosopiperidine	2	
Polychlorinated biphenyls	2	
Procarbazine	2	
1,3-Propane sulfone	2	
beta-Propiolactone	2	Y
Propylenimine	1	
Thorium dioxide	2	
m-Toluenediamine	2	
Uracil mustard	2	
Urethane	1	
Vinyl chloride	2	Y

Note 1 - The exempt quantities are defined as:

Number For Laboratory Storage For Laboratory Use

1	<1 liter or 1000 grams	<50 milliliters or 50 grams
2	<0.1 liter or 100 grams	<5 milliliters or 5 grams
3	none	none

Appendix B

LIST OF CARCINOGENS

The following are substances either known to be human carcinogens or which may reasonably be anticipated to be carcinogens (suspect carcinogens). The latest delisted substances as reported from the 10th Annual Report on Carcinogens, National Toxicology Program (2002) are also included.

"Known carcinogens" are defined as those substances for which the evidence from human studies indicates that there is a causal relationship between exposure to the substance and human cancer.

Substances which are "suspect carcinogens" are defined as those for which there is limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

The list of chemical agents and the definitions are extracted from the 10th Annual Report on Carcinogens, Summary, 2002, National Toxicology Program, Public Health Service, U.S. Department of Health and Human Services, OSHA and from IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Supplement 7, Overall Evaluation of Carcinogenicity: An Updating of IARC Monographs from Volume 1 to 82 plus, Lyon, 1987-2002.

Known Carcinogens

Aflatoxins	4-Aminobiphenyl
Alcoholic Beverage Consumption	Arsenic and arsenic compounds
Analgesic mixtures containing phenacetin	Asbestos
Aflatoxins (naturally occurring mixtures of)	4-Aminobiphenyl
Arsenic and arsenic compounds	Asbestos
Azathioprine	Benzene
Benzidine (and Dyes Metabolized to Benzidine)	Beryllium and Beryllium Compounds
Bis(chloromethyl)ether(BCME) and technical grade chloromethyl methyl ether (CMME)	1,3-Butadiene
1,4-Butanediol dimethanesulfonate (myleran)	Cadmium and Cadmium Compounds

Chlorambucil	1-(2-Chloroethyl)-3-(4-methylcyclohexyl)-1-nitrosourea (Methyl-CCNU)
Chromium [VI] compounds	Cyclosporin A (Ciclosporin)
Cyclophosphamide	Diethylstilboestrol (DES)
Environmental Tobacco Smoke	Erionite
Estrogens, Steroidal	Ethylene Oxide
Etoposide	[Gamma Radiation: see X- and Gamma (g)-Radiation]
Melphalan	Methoxsalen with ultra-violet A therapy (PUVA)
Mineral oils, untreated and mildly-treated	MOPP - (combined therapy with nitrogen mustard, vincristine, procarbazine & prednisone) and other combined chemotherapy including alkylating agents
Mustard gas (Sulfur mustard)	2-Naphthylamine
Neutrons	Nickel compounds
Radon	Oestrogen replacement therapy
Oestrogens, nonsteroidal	Oestrogens, steroidal
Oral contraceptives, combined	Oral contraceptives, sequential
Phosphorus-32, as phosphate	Plutonium-239 and its decay products (may contain plutonium-240 and other isotopes), as aerosols
Radioiodines, short-lived isotopes, including iodine-131	Radionuclides, α -particle-emitting, internally deposited
Radionuclides, β -particle-emitting, internally deposited	Radium-224 and its decay products
Radium-226 and its decay products	Radium-228 and its decay products
Radon-222 and its decay products	Silica, Crystalline (Respirable Size)
Solar Radiation (See Ultraviolet Radiation Related Exposures)	Soots

Strong Inorganic Acid Mists Containing Sulfuric Acid	Sunlamps or Sunbeds, Exposure to (See Ultraviolet Radiation Related Exposures)
Talc containing asbestiform fibres	Tamoxifen
2,3,7,8-Tetrachlorodibenzo-p-dioxin (TCDD); “Dioxin”?	Thiotepa
Thorium dioxide	Tobacco products, smokeless and Tobacco smoke
Treosulfan	Vinyl chloride
Ultraviolet Radiation, Broad Spectrum UV Radiation	Wood Dust

Suspect Carcinogens

A- α -C (2-Amino-9H-pyrido[2,3-b]indole)	Acetaldehyde
Acetamide	2-Acetylaminofluorene
Acrylamide	Acrylonitrile
Adriamycin	AF-2[2-(2-Furyl)-3-(5-nitro-2-furyl)acrylamide]
Aflatoxin M1	2-Aminoanthraquinone
1-Amino-2-methylantraquinone	<i>p</i> -Aminoazobenzene
<i>o</i> -Aminoazotoluene	2-Amino-5-(5-nitro-2-furyl)-1,3,4-thiadiazole
Amsacrine	<i>ortho</i> -Anisidine
Amitrole	Androgenic (anabolic) steroids
<i>o</i> -Anisidine and <i>o</i> -anisidine HCl	Antimony trioxide
Aristolochic acids	Azacitidine
Auramine, technical grade	Azaserine
Benz(<i>a</i>)anthracene	Benzidine-based dyes
Benzo(<i>b</i>)fluoranthene	Benzo(<i>j</i>)fluoranthene
Benzo(<i>k</i>)fluoranthene	Benzofuran
Benzo(α)pyrene	Benzyl violet 4B
Beryllium and certain Be compounds	2,2-Bis(bromomethyl)propane-1,3-diol
Bischloroethyl nitrosourea (BCNU)	Bitumens, extracts of steam-refined & air-refined
Bleomycins	Bromodichloromethane
1,3-Butadiene	Butylated hydroxyanisole (BHA)
β -Butyrolactone	Caffeic acid

Captafol	Carbon black
Carbon tetrachloride	Catechol
Carrageenan, degraded	Chlordane
Chlordecone (Kepone)	Chlorendic acid
<i>para</i> -Chloroaniline	α -Chlorinated toluenes
1-(2-Chloroethyl)-3-cyclohexyl-1-nitrosourea (CCNU)	Chloroform
1-Chloro-2-methylpropene	Chlorophenols
Chlorophenoxy herbicides	4-Chloro- <i>o</i> -phenylenediamine
Chloroprene	Chlorothalonil
4-Chloro- <i>o</i> -toluidine	Chlorozotocin
CI Acid Red 114	C.I. basic red 9 monohydrochloride
CI Direct Blue	Citrus Red No 2
Cobalt and cobalt compounds	Cisplatin
Creosotes	<i>p</i> -Cresidine
Cupferron	Dacarbazine
Dantron (Chrysazin; 1,8-Dihydroxyanthraquinone)	Daunomycin
DDT	<i>N,N'</i> -Diacylbenzidine
2,4-Diaminoanisole	3,3-Diaminobenzidine
4,4'-Diaminodiphenyl ether	2,4-Diaminotoluene
Dibenz(<i>a,h</i>)acridine	Dibenz(<i>a,j</i>)acridine
Dibenz(<i>a,h</i>)anthracene	7 <i>H</i> -Dibenzo(<i>c,g</i>)carbazole
Dibenzo(<i>a,e</i>)pyrene	Dibenzo(<i>a,h</i>)pyrene
Dibenzo(<i>a,i</i>)pyrene	Dibenzo(<i>a,l</i>)pyrene
1,2-Dibromo-3-chloropropane (DBCP)	1,2-Dibromoethane (EDB)

<i>para</i> -Dichlorobenzene	3,3'-Dichlorobenzidine
3,3'-Dichloro-4,4'-diaminodiphenyl ether	1,2-Dichloroethane (EDC)
Dichloromethane	1,3-Dichloropropene (technical grade)
1,2-Diethylhydrazine	Diepoxybutane
Di(2-ethylhexyl)phthalate	Diethyl sulfate
1,2-Diethylhydrazine	Diglycidyl resorcinol ether
Dihydrosafrole	Diisopropyl sulfate
3,3'-Dimethoxybenzidine	<i>p</i> -Dimethylaminoazobenzene
<i>t</i> -2-[(Dimethylamino)methylimino]-5-[2-(5-nitro-2-furyl)vinyl]-1,3,4-oxadiazole	2,6-Dimethylaniline(2,6-Xylidine)
3,3'-Dimethylbenzidine (<i>ortho</i> -Tolidine)	Dimethylcarbamoyl chloride
1,1-Dimethylhydrazine	1,2-Dimethylhydrazine
3,7-Dinitrofluoranthene	3,9-Dinitrofluoranthene
1,6-Dinitropyrene	1,8-Dinitropyrene
2,4-Dinitrotoluene	2,6-Dinitrotoluene
Dimethyl sulfate	Dimethylvinyl chloride
1,4-Dioxane	Direct Black 38 (benzidine derived azo dye)
Direct Blue 6	Disperse Blue 1
1,2-Epoxybutane	Epichlorohydrin
Ethylbenzene	Ethyl methanesulfonate
<i>N</i> -Ethyl- <i>N</i> -nitrosourea	Ethylene dibromide
Ethylene oxide	Ethylene thiourea
Etoposide	Formaldehyde

2-(2-Formylhydrazino)-4-(5-nitro-2-furyl)thiazole	Fumonisin B1
Furan	Glycidaldehyde
Glu-P-1(2-Amino-6-methyldipyrido[1,2-a:3',2'-d]imidazole	Glu-P-2(2-Aminodipyrido[1,2-a:3',2'-d]imidazole
Glycidol	Griseofulvin
HC Blue No. 1	Heptachlor
Hexachlorobenzene	Hexachlorocyclohexanes
Hexachloroethane	Hexamethylphosphoramide
Hydrazine and hydrazine sulfate	1-Hydroxyanthraquinone
Hydrazobenzene	Indeno [1,2,3,- <i>cd</i>]pyrene
Iron-dextran complex	IQ (2-Amino-3-methylimidazo[4,5- <i>f</i>]quinoline)
Isoprene	Lasiocarpine
Lead and lead compounds, inorganic	MeA- α -C (2-Amino-3-methyl-9 <i>H</i> -pyrido[2,3- <i>b</i>]indole)
Magenta	Medroxyprogesterone acetate
MeIQ(2-Amino-3,4-dimethylimidazo[4,5- <i>f</i>]quinoline)	MeIQx(2-Amino-3,8-dimethylimidazo[4,5- <i>f</i>]quinoxaline)
Merphalan	5-Methoxypsoralen
2-Methylaziridine (propyleneimine)	Methylazoxymethanol & its acetate
5-Methylchrysene	4,4'-Methylene bis(2-chloroaniline) (MOCA)
4,4'-Methylene bis(2-methylaniline)	4,4'-Methylenedianiline
Methylmercury compounds	Methyl methanesulfonate
2-Methyl-1-nitroanthraquinone	<i>N</i> -Methyl- <i>N'</i> -nitro- <i>N</i> -nitrosoguanidine (MNNG)
<i>N</i> -Methyl- <i>N</i> -nitrosourea	<i>N</i> -Methyl- <i>N</i> -nitrosourethane
4,4'-Methylene bis(<i>n,n</i> -dimethyl)benzeneamine	4,4'-Methylenedianiline & its dihydrochloride

Methylthiouracil	Metronidazole
Michler's ketone	Mirex
Mitomycin C	Mitoxantrone
Monocrotaline	5-(Morpholinomethyl)-3-[(5-nitrofurfurylidene)amino]-2-oxazolidinone
Nafenopin	Naphthalene
Nickel, metallic and alloys	Niridazole
Nitrilotriacetic acid and its salts	5-Nitroacenaphthene
2-Nitroanisole	Nitrobenzene
6-Nitrochrysene	Nitrofen
2-Nitrofluorene	1-[(5-Nitrofurfurylidene)amino]-2-imidazolidinone
<i>N</i> -[4-(5-Nitro-2-furyl)-2-thiazolyl]acetamide	Nitrogen mustard
Nitrogen mustard <i>N</i> -oxide	Nitromethane
2-Nitropropane	1-Nitropyrene
4-Nitropyrene	<i>N</i> -Nitrosodi- <i>n</i> -butylamine
<i>N</i> -Nitrosodiethanolamine	<i>N</i> -Nitrosodiethylamine
<i>N</i> -Nitrosodimethylamine	<i>N</i> -Nitrosodi- <i>n</i> -propylamine
<i>N</i> -Nitroso- <i>n</i> -ethylurea	3-(<i>N</i> -Nitrosomethylamino)propionitrile
4-(<i>N</i> -Nitrosomethylamino)-1-(3-pyridyl)-1-butanone(NNK)	<i>N</i> -Nitrosomethylethylamine
<i>N</i> -Nitrosomethylvinylamine	<i>N</i> -Nitroso- <i>n</i> -methylurea
<i>N</i> -Nitrosomorpholine	<i>N'</i> -Nitrosornicotine
<i>N</i> -Nitrosopiperidine	<i>N</i> -Nitrosophyrrolidine
<i>N</i> -Nitrososarcosine	Norethisterone

Ochratoxin A	Oil Orange SS
4,4-Oxydianiline	Oxazepam
Oxymetholone	Palygorskite (attapulgate) (long fibres, > 5 micrometers)
Panfuran S (containing dihydroxymethylfuratrizine)	Phenacetin
Phenazopyridine and HCl-salt	Phenobarbital
Phenolphthalein	Phenoxybenzamine hydrochloride
Phenyl glycidyl ether	Phenytoin
PhIP(2-Amino-1-methyl-6-phenylimidazo[4,5- <i>b</i>]pyridine)	Polybrominated biphenyls (PBBs)
Polychlorophenols and their sodium salts	Polychlorinated biphenyls (PCBs)
Ponceau MX	Ponceau 3R
Potassium bromate	Procarbazine and HCl-salt
Progestins	Progestogen-only contraceptives
1,3-Propane sultone	β -Propiolactone
Propylene oxide	Propylthiouracil
Refractory ceramic fibres	Riddelliine
Reserpine	Safrole
Selenium sulfide	Silica, crystalline
Sodium <i>o</i> -phenylphenate	Sterigmatocystin
Streptozotocin	Styrene
Styrene-7,8-oxide	Sulfallate
2,3,7,8-Tetrachlorodibenzo- <i>p</i> -dioxin (TCDD)	Tetrachloroethylene
Tetrafluoroethylene	Tetranitromethane
Thioacetamide	4,4'-Thiodianiline

Thiouracil	Thiourea
Toluene diisocyanates	<i>o</i> -Toluidine and <i>o</i> -toluidine-HCl
Toxaphene (Polychlorinated camphenes)	Trichlormethine (Trimustine hydrochloride)
2,4,6-Trichlorophenol	Tris(1-aziridiny)phosphine sulfide
Tris(2,3-dibromopropyl)phosphate	Trp-P-1(3-Amino-1,4-dimethyl-5 <i>H</i> -pyrido[4,3- <i>b</i>]indole)
Trp-P-2(3-Amino-1-methyl-5 <i>H</i> -pyrido[4,3- <i>b</i>]indole)	Trypan blue
Uracil mustard	Urethane
Vinyl acetate	Vinyl bromide
4-Vinylcyclohexene	4-Vinylcyclohexene diepoxide
Zalcitabine	Zidovudine (AZT)

Delisted Carcinogens

Substance Name	CAS Number	Last Listing Reported by NTP	Reason for Delisting
Chloramphenicol	56-75-7	known carcinogen First Report (1980)	Human data considered inadequate
Aramitefi	140-57-8	reasonably anticipated carcinogen Fourth Report (1985)	No U.S. residents exposed
N,N-bis(2-Chloroethyl)-2-naphthylamine (Chlornaphazine)	494-03-1	known carcinogen Fourth Report (1985)	No U.S. residents exposed
Cycasin	14901-08-7	reasonably anticipated carcinogen Fourth Report (1985)	No U.S. residents exposed
Methyl iodide	78-88-4	reasonably anticipated carcinogen Fourth Report (1985)	Re-evaluated by IARC; now considered "equivocal"
5-Nitro- <i>o</i> -anisidine	99-59-2	reasonably anticipated carcinogen Fifth Report (1989)	Insufficient evidence of carcinogenicity
<i>p</i> -Nitrosodiphenylamine	156-10-5	reasonably anticipated carcinogen Fifth Report (1989)	Insufficient evidence of carcinogenicity

Ethyl acrylate	140-88-5	reasonably anticipated carcinogen Eighth Report (1998)	Does not meet the criteria to be listed
Saccharin	81-07-2	reasonably anticipated carcinogen Eighth Report (1998)	Does not reasonably anticipated to be a human carcinogen under conditions of general usage as an artificial sweetener

Appendix C

OSHA's LABORATORY HEALTH STANDARD

"Occupational Exposures to Hazardous Chemicals in Laboratories"

29 CFR 1910.1450

The Laboratory Health Standard requires laboratories to develop procedures which help to ensure that occupational exposure to hazardous chemicals in the laboratory environment is reduced or minimized.

OSHA summarizes the intent of the standard in the preamble:

"The new standard differs from many OSHA health standards in that it does not establish new exposure limits, but sets other performance provisions designed to protect laboratory workers from potential hazards in their work environment. By permitting a greater degree of flexibility to laboratories in developing and implementing employee safety and health programs, OSHA expects benefits to result from increased worker awareness of potential risks, improved work practices, appropriate use of existing personal protective equipment and greater use of engineering controls. Given the flexibility to design and implement innovative measures to reduce employee exposure to hazardous substances, employers also will reap rewards in terms of lower insurance premiums, lower property damage costs, lower turnover costs, less absenteeism and, in general, increased productivity. Finally, the potential decrease in acute and chronic health problems will result in overall benefits to society through the associated reduction in medical and productivity costs."

This quote summarizes the basic goals and approach of the Laboratory Health Standard. It is primarily a performance oriented standard, allowing individual laboratories to tailor their approaches to meeting the requirements of the standard to their individual circumstances.

The text of the standard, including the appendices, is included for reference purposes into this Chemical Hygiene Plan.

Link to Federal Standard: [Occupational Exposures to Hazardous Chemicals in Laboratories](#)

Appendix D

LABORATORY CHEMICAL HYGIENE PLAN

LABORATORY SAFETY REFERENCE MATERIAL

The following are good chemical safety and general laboratory safety references. Those with a CALL #, are available through the Snell Library.

1. Corp author OSHA, *Employer rights and responsibilities following an OSHA inspection*, Washington, DC: The Administration, Latest Received: Year 2002 [CALL # L 35.2: EM 7/3].
2. Gottschall, WC, Walters, DB *Laboratory health and safety dictionary*, New York: Wiley, 2001. [CALL # QD63.5.G67 2001, ISBN 0471283177].
3. Wood, JP ed. *Containment in the pharmaceutical industry*. New York: Dekker, c2001. [CALL # HD9665.5.C663 2001, ISBN 0824703979].
4. *Assessing the need for personal protective equipment: A guide for small business employers*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration, 2000. [CALL # L35.8:EQ 5/2000].
5. *Access to medical and exposure records*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration, Edn. Rev. 2001. [CALL # L 35.2:M 46/2001].
6. Corp author OSHA, *Hazard communication guidelines for compliance*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration: For sale by the US G.P.O., Supt. of Docs; 2000. [CALL # L35.8:H 33/2000, ISBN 0160497302].
7. Corp author OSHA, *All about OSHA*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration, Identity 000001, L 35.2:OC 1/2/ LIB HAS, Latest Received: 2000, [CALL # L 35.2: OC 1/2].
8. *Environmental management guide for small laboratories*. Washington, DC: US Environmental Protection Agency, Small Business Division, 2000. [CALL # EP1.8:M 31/5].
9. Furr, AK *CRC handbook of laboratory safety*, Boca Raton: CRC Press, 5th Edn., c2000.[CALL # QD51.H27 2000, ISBN 0849325234].
10. Report, John MD et al. *Conference Chemical and Biological Respiratory Protection Workshop* (1999: Morgantown, WV), NIOSH-DOD-OSHA sponsored *Chemical and Biological Respiratory Protection Workshop*, Atlanta, GA: US Dept. of Health and Human Services, Public Health

- Service, Centers for Disease Control and Prevention, National Institute for Occupational Safety and Health, 2000. [CALL # HE20.7102: W 89/10].
11. May, W et. al. *Definitions of terms and modes used at NIST for value-assignment of reference materials for chemical measurements [microform]*, Gaithersburg, MD: US Dept. of Commerce, Technology Administration, National Institute of Standards and Technology; Washington, DC: For sale by the Supt. of Docs., US G.P.O., 2000. [CALL # C 13.10:260-136, ISBN 0160590159].
 12. Corp author EPA and OSHA, *EPA/OSHA joint chemical accident investigation report [microform]: BPS, Inc.*, West Helena, Arkansas. Washington, DC: US Environmental Protection Agency and US Occupational Safety and Health Administration, 1999, [CALL # Snell Microform Index EP 1.2: C 42/33].
 13. Corp author OSHA, *OSHA inspections*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration, [CALL # L 35.2: IN 7].
 14. Corp author OSHA, *OSHA technical manual [computer file]*. Washington, DC: Occupational Safety & Health Administration, 1999, [CALL # L 35.8: IN 7/999].
 15. Corp author OSHA, *Screening and surveillance: A guide to OSHA standards*. Washington, DC: U.S. Dept. of Labor, Occupational Safety and Health Administration; For sale by U.S. G.P.O., Supt. of Docs., 1999. [CALL # L35.8: SCR 2, ISBN 0160501164].
 16. Author OSHA *Industrial hygiene*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration, 1998. [CALL # L35.2:H 99/998].
 17. Corp author OSHA and Eastern Research Group, Inc., *Small entity compliance guide for the revised respiratory protection standard*. Washington, DC: US Dept. of Labor, Directorate of Health Standards Programs, Occupational Safety and Health Administration, 1998. [CALL # L35.8:EN 8].
 18. Long, H. Keith, Daddow, Richard L. and Farrar, Jerry W. *US Geological Survey Standard Reference Sample Project--performance evaluation of analytical laboratories*. Reston, VA: US Geological Survey, US Dept. of the Interior, 1998. [CALL # I19.127:031-98, USGS fact sheet; FS-031-98].
 19. Corp author OSHA, *Training requirements in OSHA standards and training guidelines*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration: For sale by the U.S. G.P.O., Supt. of Docs., 1998. [CALL # L35.8:T 68/998, Rev. Edn 1998, (ISBN 0160497310)].

20. Corp author EPA and OSHA, *EPA/OSHA joint chemical accident investigation report [microform]: Napp Technologies, Inc.*, Lodi, NJ, Washington, DC: US Environmental Protection Agency: US Occupational Safety and Health Administration, 1997, [CALL # EP 1.2: J 66].
21. Corp author OSHA, *Hazardous waste operations and emergency response*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration, 1997. [CALL # L 35.2: H 33/3/997].
22. Armour, MA *Hazardous laboratory chemicals disposal guide*, Boca Raton, FL: CRC/Lewis Publishers, c1996. [CALL # QD64.A76 1996, ISBN 1566701082].
23. Corp author OSHA, *OSHA handbook for small businesses*. Washington, DC: US Dept. of Labor, Occupational Safety and Health Administration: For sale by the US G.P.O. Supt. of Docs., 1996. [CALL # HD2346.U5 U52 1996, ISBN 016048832X].
24. *Conference Federal Safety and Health Conference (51st: 1996: Orlando, Fla.) 51st annual Federal Safety and Health Conference program [microform]: theme, sharing ideas: Orlando, FL, 1996: presented by OSHA*, Washington, DC: The Administration, 1996. [CALL # L 35.2: SH 2].
25. Hathaway, GJ, Proctor, NH, Hughes, JP eds. *Chemical hazards of the workplace*, New York: Van Nostrand Reinhold, 4th Edn. 1996. [CALL # RA1229.P76 1996, ISBN 0442020503].
26. Koren, H, Bisesi, MS *Handbook of environmental health and safety: principles and practices*. Boca Raton: Lewis Publishers, 3rd Edn. c1996. [CALL # RA565.K67 1996 v.1 and RA565.K67 1996 v.2, ISBN 1566701244 (v. 1) and 1566701252 (v. 2)].
27. Clayton, GD, Allan, RE, Florence, EC, Patty's Patty, FA *Industrial hygiene and toxicology*, New York: Wiley, 4th Edn. c1991-1995. [CALL # RC967.P37 1991 v.1 ptA; RC967.P37 1991 v.2 ptB; RC967.P37 1991 v.2 ptC; RC967.P37 1991 v.3 ptA; RC967.P37 1991 v.2 ptf; RC967.P37 1991 v.2 ptD; RC967.P37 1991 v.2 ptE; RC967.P37 1991 v.3 ptB; RC967.P37 1991 v.1 ptB; ISBN 0471501972 (v. 1, pt. A)].
28. Bisesi, MS, Kohn, JP *Industrial hygiene evaluation methods*. Boca Raton: Lewis Publishers, c1995. [CALL # RC967.B53 1995, ISBN 1566700248].
29. Harrison, LL ed. in chief, *Environmental, health, and safety auditing handbook*. New York: McGraw-Hill, 2nd Edn., c1995. [CALL # HD30.255.E58 1995 and HD30.255.E58 1995 Supp, ISBN 0070269041].

30. Stricoff, RS, Walters, DB *Handbook of laboratory health and safety*, New York: Wiley, 2nd Edn., c1995. [CALL # QD51.S92 1995, ISBN 047102628X].
31. Cartledge, B ed., *Health and the environment*. New York: Oxford University Press, 1994. [CALL # RA565.H383 1994, ISBN 0198584180: and 0198584172].
32. Barton, J, Rogers, R eds. *Chemical reaction hazards: A guide*. Rugby, Warwickshire, UK: Institution of Chemical Engineers, c1993. [CALL # TP149.C53 1993, ISBN 0852952848]
33. McMichael, AJ *Planetary overload: Global environmental change and the health of the human species*. New York: Cambridge University Press, 1993. [CALL # RA565.M384 1993, ISBN 0521441382].
34. Parkany, M ed. *Conference International Symposium on the Harmonization of Internal Quality Assurance Schemes for Analytical Laboratories* (5th: 1993: Washington, DC) Cambridge: The Royal Society of Chemistry, c1993. [CALL # QD75.4.Q34 I55 1993, ISBN 0851867057].
35. Authors IUOPAC and International Programme on Chemical Safety; *Chemical safety matters*. New York: Cambridge University Press, 1992. [CALL # QD63.5.C47 1992, ISBN 0521413753].
36. Bach, PH et al. Tel-A-Train, inc. *Chemical safety in the laboratory [videorecording]* Chatanooga, TN: Tel-A-Train, c1992. [CALL # MV7-3647r].
37. Moeller, DW *Environmental health*. Cambridge, MA: Harvard University Press, 1992. [CALL # RA565.M64 1992, ISBN 0674258584].
38. Armour, M A *Hazardous laboratory chemical disposal guide*, Boca Raton, FL: CRC Press, c1991. [CALL # QD64.A76 1991, ISBN 084930265X].
39. Author OSHA Directorate of Compliance Programs. *OSHA systems safety inspection guide*. Rockville, MD: Government Institutes, Inc., 1991. [CALL # T55.3.H3 U54 1991, ISBN 0865877645].
40. Corp author OSHA, *OSHA CD-ROM [computer file]*. Washington, DC: OSHA, 1991- [CALL # L 35.26, ISBN 1065-9277].
41. Mahn, WJ *Academic laboratory chemical hazards guidebook*, New York: Van Nostrand Reinhold, c1991. [CALL # QD51.M29 1991, ISBN 0442001657].
42. Ockerman, HW *Illustrated chemistry laboratory terminology*, Boca Raton, FL: CRC Press, c1991. [CALL # QD51.O25 1991, ISBN 0849301521].

43. Corp author OSHA, *OSHA regulated hazardous substances: Health, toxicity, economic, and technological data*. Park Ridge, NJ, USA: Noyes Data Corporation, c1990. [CALL # T55.3.H3 O79 1990 v.1, T55.3.H3 O79 1990 v.2, ISBN 0815512406].
44. Everett, K *Guidance on laboratory fume cupboards*. London: the Royal Society of Chemistry, 1990. [CALL # QD51.G8 1990, ISBN 0851863299].
45. Kaufman, JA ed. *Waste disposal in academic institutions*, Chelsea, MI: Lewis Publishers, c1990. [CALL # QD64.W37 1990, ISBN 0873712560].
46. American Conference of Governmental Industrial Hygienists. *Guide to Occupational Exposure Values*. American Conference of Governmental Industrial Hygienists, Inc. Cincinnati, OH, 1990.
47. Stricoff, RS, Walters, DB *Laboratory health and safety handbook: A guide for the preparation of a chemical hygiene plan*, New York: Wiley, c1990. [CALL # QD51.S92 1990, ISBN 0471617563].
48. Young, JA, Kingsley, WK, Wahl, Jr. GH *Developing a chemical hygiene plan*, Washington, DC: American Chemical Society, 1990. [CALL # QD51.Y68 1990, ISBN 0841218765].
49. Furr, AK ed. *CRC Handbook of Laboratory Safety, 3rd ed.* CRC Press, Boca Raton, Florida. 1989.
50. Scott, RM *Chemical hazards in the workplace*. Chelsea, MI: Lewis Publishers, c1989. [CALL # RA1229.S39 1989, ISBN 0873711343].
51. Garner, WY, Barge, MS eds. *Good laboratory practices: An agrochemical perspective*, The 194th Meeting of the American Chemical Society, New Orleans, Louisiana, 1987, Washington, DC: ACS, 1988. [CALL # QD51.G66 1988, ISBN 0841214808].
52. Young, JA ed. *Improving Safety in the Chemical Laboratory a Practical Guide*. John Wiley and Sons, New York. 1987.
53. Sax, NI, Lewis, RJ *Hawley's Condensed Chemical Dictionary*, 11th Edn. New York: Van Nostrand Reinhold Co. 1987.
54. Sax, NJ, Lewis, RJ eds. *Rapid Guide to Hazardous Chemical in the Workplace*. New York: Van Nostrand Reinhold Company, 1986.
55. US Department of Health and Human Services. *NIOSH/OSHA Pocket Guide to Chemical Hazards*. NIOSH Pub. No. 85-114, US Government Printing Office, Washington, DC September 1985 (or latest edition).

56. Pipitone, AA ed. *Safe Storage of Laboratory Chemicals*. New York: Wiley, 1984.
57. American Conference of Governmental Industrial Hygienists. *Guidelines for the Selection of Chemical Protective Clothing*, 1983.
58. National Research Council. *Prudent Practices for Handling Hazardous Chemicals in the Laboratories*. National Academy Press. Washington, DC, 1983.
59. National Research Council. *Prudent Practices for Disposal of Chemicals from Laboratories*. Washington, DC, 1983.
60. Clayton, GD, Clayton, FL eds. *Patty's Industrial Hygiene and Toxicology. General Principles, Vol. I through III*. New York: Wiley Interscience, 1982.
61. Freeman, NT, Whitehead, J eds. *Introduction to Safety in the Chemical Laboratory*. New York: Academic Press, 1982.
62. National Fire Protection Association. *Fire Protection for Laboratories Using Chemicals* NFPA-45, 1982. *Safety Standards for Laboratories in Health Related Institutions*, NFPA-56C, 1980. NFPA, Batterymarch Park, Quincy, MA 02269.
63. Choudhary, G ed. *Chemical hazards in the workplace: Measurement and control*, Washington, DC: American Chemical Society, 1981. [CALL # RA1229.C46, ISBN 0841206082].
64. Fuscaldo, AA, Erlick, BJ, Hindman, B eds. *Laboratory Safety Theory and Practice*. Academic Press. 1980.
65. Koren, H *Handbook of environmental health and safety: Principles and practices*. New York: Pergamon Press, c1980. [CALL # RA565.K67 1980, ISBN 0080239005].
66. Braker, W, Mossman, AL, Siegel, D eds. *Effects of Exposure to Toxic Gases - First Aid and Medical Treatment, 2nd ed*. New Jersey: Matheson, ,1979.
67. Bretherick, L ed. *Handbook of Reactive Chemical Hazards*. Butterworths. 1979.
68. Kunze, LJ, Murphy, RA, Briggs, HJ Ferris, TN *Chemical technicians*, Cleveland, OH: Education Research Council of America, 1978. [CALL # HF5381.2.R43 serF 9.2].

69. Leh, FKV, Lak, RKC *Environment and pollutions: Sources, health effects, monitoring, and control*. Springfield, IL: Thomas, 1974. [CALL # RA565.L43, ISBN 0398030308].
70. Lee, DHK ed. *Metallic contaminants and human health*. New York: Academic Press, 1972. [CALL # RA565.M47 1972, ISBN 0124406602].
71. Manufacturing Chemists Association. *Guide for Safety in the Chemical Laboratory*, 2nd Edn. Van Norstrand Reinhold Company. 1972.
72. McLaughlin, T *Dirt; a social history as seen through the uses and abuses of dirt*. New York: Stein and Day, 1971. [CALL # RA565.M33, ISBN 0812814126].
73. Bretherick, L ed. *Hazards in the Chemical Laboratory*. London: Royal Society of Chemistry, Burlington House.
74. American Conference of Governmental Industrial Hygienists. *Threshold Limit Values and Biological Exposure Indices*. ACGIH, P.O. Box 1937, Cincinnati, OH 45201.
75. Code of Federal Regulations, 29 CFR part 1910 subpart Z. U.S. Government Printing Office. Washington, DC 20402.

Appendix E

QUESTIONS AND ANSWERS CONCERNING:

OSHA'S LABORATORY STANDARD: 29 CFR 1910.1450

In General: If an employer with laboratories is undecided whether to follow OSHA's Hazard Communication Standard or its Laboratory Standard, OSHA has indicated that it would rather have the Laboratory Standard complied with, as it is considered to be more comprehensive in its requirements for laboratories.

If a company's quality control laboratories have been following all parts of the Laboratory Standard, the OSHA National Office considers it unlikely that an inspector would give them more than a *de minimis* citation.

1. **Q. Does OSHA's Laboratory standard cover quality control laboratories?**

A. Not if they do standardized, routine analytical work that is tied in with production operations. Much depends on the nature of the work done by the laboratory and the degree of compliance.

The repetitive nature of the laboratory operation or the lack of variability of the chemicals used are not part of the definition of laboratory use or laboratory scale. These factors were merely discussed in the preamble to the regulations as characteristics frequently found in laboratories and one of the many elements that influenced the Agency's decision to have a separate standard on laboratories.

The preamble to the final rule indicates that "most quality control laboratories are not expected to meet the qualification for coverage under the Laboratory Standard" (55 FR at 3312) because they are typically adjuncts of production operations. However, this is a question of fact, and each particular quality control laboratory must be evaluated within the context of its industrial operation.

Clearly there may be some circumstances where a laboratory, even though it may be called a quality control laboratory, meets all of the elements included in the definitions of "laboratory use" and "laboratory scale" and would therefore be considered to be within the scope of the Laboratory Standard.

2. **Q. Definition of Quality Control Laboratory:** How is a quality control laboratory defined as compared to a laboratory that would be covered by 1910.1450?

A. If the laboratory performs routine, standardized tests which monitor and support production processes, it can be considered as a quality control laboratory.

3. **Q. Sophisticated Quality Control Laboratories:** Some quality control laboratories are quite sophisticated, using gas chromatography and mass spectrometry for the analysis performed. They use chemicals in very small amounts, and the employees performing the analysis are all trained chemists. Should these labs follow the requirements of 1910.1450 the Laboratory Standard or those of the Hazard Communication Standard?

A. If non-routine, non-production related tests are performed using the laboratory's sophisticated analytical instruments, this occurrence would initiate and require compliance with 29 CFR 1910.1450. The answer is yes.

4. **Q. MSDS For Mailed Research Samples:** Serious concerns have been raised over the interpretation of Section (h) (2) (iii), Hazard Identification. Section (iii) seems to require that if the chemical of concern is being sent to another user outside the producing laboratory, an MSDS must be prepared and sent along with it. Many industrial research laboratories routinely send out samples of experimental chemicals for testing and analysis. Most laboratories that send samples of research chemicals to another laboratory produce a full MSDS prior to sending the chemical?

A. Prior to the promulgation of the Laboratory Standard, laboratories had certain obligations under the Hazard Communication Standard. The same obligations still apply when a chemical is to be shipped to another user. The intent of the paragraph in the laboratory standard is to state that the Laboratory Standard does not exempt laboratories from requirements of the Hazard Communication Standard, with respect to MSDS's and labeling, when a substance is to be sent out.

If a laboratory has been in compliance with Hazard Communication Standard requirements, nothing need change in this regard. If the document stating the hazards of the chemical has satisfied the requirements of Hazard

Communication prior to promulgation of the Laboratory Standard, it will continue to do so.

5. **Q. Service Personnel In Laboratories:** Where a laboratory has service personnel such as janitors, or people delivering solvents, chemicals etc., do these people fall under the requirements of the Laboratory Standard or the HCS?

A. Service personnel who do not work in a research laboratory consistently, would be covered by the Hazard Communication Standard.

6. **Q. What Does The Laboratory Standard Supersede?** Section (a)(2) says that the Laboratory Standard supersedes all other OSHA Health Standards except for the (1) skin and eye contact, (2) PEL's, (3) Action Levels: Does this concept apply equally to all parts of other OSHA health and safety standards?

A. Yes, but if required monitoring shows consistent exposures above an Action Level, then the same exposure monitoring and medical surveillance provisions as in the relevant substance specific standard will apply.

7. **Q. Contact Lenses:** Section E,1,(k), Personal protection, (Appendix A) recommends that the use of contact lenses be avoided unless special precautions are taken: (1) Does OSHA officially discourage the use of contact lenses in the laboratory? and (2) What special precautions does OSHA want where contact lenses are worn in the laboratory?

A. (1) OSHA's present policy does not have a problem with the wearing of contact lenses in the laboratory providing proper eye protection is worn when appropriate. Some compliance officers will give a de minimis citation for the use of contact lenses, others ignore it entirely.

(2) OSHA wants increased attention paid to the use of protective eyewear in the laboratory for all workers, particularly those who wear contact lenses.

8. **Q. Defining High Degree of Acute Toxicity:** The new laboratory standard 29 CFR 1910.1450, has requirements for additional employee protection for work with particularly hazardous substances as detailed in Section

(e)(3)(viii) of the standard. This section states that particularly hazardous substances include those substances which have a "high degree of acute toxicity". The phrase "high degree of acute toxicity" is undefined in the standard and is subject to wide variation in interpretation. Guidance is requested concerning interpretation of this phrase.

A. Although there are some basic differences between the Hazard Communication Standard (HCS) and the laboratory standard, the Laboratory Standard tries to be consistent with HCS definitions.

The HCS delineates between "acute" and "chronic" on the basis of severity or duration of effects and states that acute effects usually occur rapidly as a result of short-term exposures and are of short durations. The HCS also defines explicitly the terms "highly toxic" and "toxic" as they relate to chemicals. Examples given are substances such as hydrogen cyanide, hydrogen sulfide, and nitrogen dioxide.

Therefore, substances that are considered to have a high degree of acute toxicity are those substances which are highly toxic, or toxic as defined under the HCS, and may be fatal or cause damage to target organs, as a result of a single exposure or exposures of short duration.

9. **Q. Physicians Written Opinion:** Paragraph (g)(4) requires that for any medical examination or consultation required by 1910.1450, a written physicians opinion be obtained. Where the examining physician finds a health impairment not due to occupational exposure, but which may predispose the individual to increased risk from exposure to chemicals, how specific should the examining physician be in the written opinion?

A. The physician should indicate the general nature of the impairment (for example, weakened immunity or decreased lung capacity) and not reveal specific illnesses, such as AIDS or emphysema.

10. **Q. Pharmacy Operations:** Does OSHA's Laboratory Standard apply to a pharmacy operation where standard formulations of cytotoxic drugs are regularly mixed?

A. The determination of whether the Laboratory Standard applies is dependent on both "laboratory use" and "Laboratory Scale" criteria. A pharmacy operator mixing cytotoxic drugs does not meet the "laboratory use" criteria because the operation simulates a production process. Laboratories generally have many hazardous chemicals present to which

exposures are intermittent rather than a few substances to which there are regular exposures.

11. **Q. Academic Laboratories:** Is it OSHA's intent to apply 1910.1450 to an academic chemistry laboratory at the high school or college level? (In most cases the Chemical Hygiene Officer and the employee would be one and the same person.)

A. Yes, OSHA intends for 1910.1450 to apply to laboratories in academic institutions. The preamble of the Laboratory Standard even included a projected annual cost of compliance with the Laboratory Standard for academic laboratories (page 3308 of January 31, 1990, Federal Register).

Appendix F

DEPARTMENT STANDARD OPERATING PROCEDURES

For certain hazards and classes of chemicals not covered under the General Standard Operating Procedures For Working with Chemicals, principal investigators and Department Safety Officers/laboratory supervisors must develop their own site specific standard operating procedures. These site specific standard operating procedures must be kept in this appendix with your hard copy of the Laboratory Chemical Hygiene Plan.